

# **TAKEUCHI<sup>®</sup>**

## **2016 MACHINE PRICE LIST**

519 Bonnie Valentine Way, Pendergrass, GA 30567

e-mail [sales@takeuchi-us.com](mailto:sales@takeuchi-us.com)  
[www.takeuchi-us.com](http://www.takeuchi-us.com)

Prices and specifications  
subject to change without notice

Prices are F.O.B. Pendergrass, GA  
Effective 1 January 2016



# TB210R

## Compact Excavator

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725

www.takeuchi-us.com

### STANDARD EQUIPMENT

- |                                  |  |
|----------------------------------|--|
| Operating Weight: 2,370 lbs.     | ROPS/TOPS 2 post foldable canopy                                 |
| Width: 29.5" / 40.2"             | Hydraulically retractable track frame                            |
| Maximum Dig Depth: 5' 9.1"       | Adjustable width dozer blade with 2 pin-on extensions            |
| Bucket Digging Force: 2,518 lbs. | Pilot operated joystick controls with safety lock out            |
| Horsepower / RPM: 11.7 / 2,200   | Control pattern change valve                                     |
| Travel Speed: 1.2 / 2.3 mph      | Two-way auxiliary hydraulic circuit routed to the end of the arm |
| Auxiliary Flow: 5.8 gpm          | Adjustable seat with 2" retractable seat belt                    |
| Boom swing: Left 85° / Right 85° | Two speed travel   |
| 7.1" wide rubber tracks          | Travel alarm   |
|                                  | Boom mounted work light  |
|                                  | Horn   |
|                                  | Cast iron, wrap around counterweight                             |

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB210R	TB210R Equipped with ROPS/TOPS 2-post foldable canopy, Rubber tracks, Travel alarm, Auxiliary hydraulics	\$24,750

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB00708	8" Bucket with teeth, .8 cu. ft. capacity	\$360
BTB00712	12" Bucket with teeth, 1.1 cu. ft. capacity	\$380

# TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

# TB216

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 3,902 lbs.	ROPS/TOPS/FOPS 4 post canopy
Width: 38.6" / 51.2"	LCD gauge panel with multi-functional operator information center
Maximum Dig Depth: 7' 9.1"	Hydraulically retractable track frame
Bucket Digging Force: 4,250 lbs.	Travel alarm
Horsepower / RPM: 15 / 2,400	Two-speed travel with automatic down shift
Travel Speed: 1.4 / 2.6 mph	Control pattern selector valve
Auxiliary Flow: 8.9 gpm	Pilot operated joystick controls with safety lock out
Boom swing: Left 80°/ Right 50°	Cast iron, wrap around counterweight
9" wide rubber tracks	Adjustable suspension seat with 2" retractable seat belt
Long Arm w/ integrated thumb mount	Two-way auxiliary hydraulic circuit routed to the end of the arm
	Variable displacement axial piston main hydraulic pumps
	Adjustable width dozer blade
	Electronic engine monitoring system

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB216	TB216 Equipped with ROPS/TOPS/FOPS canopy, Rubber tracks	\$32,526

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	\$465
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	\$480
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	\$557
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	\$650
BQC01600	Quick Coupler	\$785
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	\$480
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	\$557
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	\$650
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	\$882
BTH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	\$2,025

### FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	\$73
BTH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	\$1,680

# TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

# TB230

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 6,607 lbs. Width: 4' 9" Maximum Dig Depth: 10' 2" Bucket Digging Force: 6,471 lbs. Horsepower / RPM: 24.4 / 2,400 Travel Speed: 1.7 / 3.0 mph Auxiliary Flow: 13.4 gpm Boom Swing: Left 80° / Right 60° Track Width: 11.8"  Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float	TOPS/ROPS/FOPS 4 post canopy Color gauge panel with multi-function operator information center High back adjustable suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 compliant engine with engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door High capacity radiator and hydraulic oil cooler Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continous detent mode Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights Varivable displacement axial piston pump Auto Idle
---	--

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB230	TB230 Canopy Equipped with Rubber Tracks	\$42,127
TB230A (w/Angle Blade)	TB230 Canopy (above Equipped) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$44,960

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB12512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$650
BTB12518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$675
BTB12524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12500	Quick Coupler	\$785
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$650
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$675
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$675
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,015
BTH125I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$1,920

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH125K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$1,575

# TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

# TB240

## Compact Excavator

### STANDARD EQUIPMENT

Operating Weight: 8,289 lbs.	TOPS/ROPS/FOPS 4 post canopy
Width: 5' 8.5"	Color gauge panel with multi-function operator information center
Maximum Dig Depth: 11' 6"	High back adjustable suspension seat
Bucket Digging Force: 9,959 lbs.	Pilot operated joystick control with control pattern change valve
Horsepower / RPM: 35.8 / 2,200	EPA Final Tier 4 compliant engine with DPF and engine monitoring system
Travel Speed: 1.7 / 3.0 mph	Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Auxiliary Flow: 17.1 gpm	Side by side industrial type radiator and hydraulic oil cooler
Boom Swing: Left 76°/ Right 58°	Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continous detent mode
Track width: 13.8"	Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, and lights
Two speed travel with automatic shift down	Variable displacement axial piston pump
Reinforced arm w/ Integrated thumb mount	Auto Idle
Heavy duty dozer blade with float	

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB240	TB240 Canopy Equipped with Rubber or Steel Tracks	\$54,343
TB240A (w/Angle Blade)	TB240 Canopy (above Equipped) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$57,433

TB240C	TB240 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet	\$61,903
TB240CA (w/ Angle Blade)	TB240 Cab (above Equipped) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$64,993

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$650
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$675
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC13500	Quick Coupler	\$785
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$650
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$675
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$675
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,015
BTH135I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$1,920

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH135K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$1,575
1914054391A	Bolt on rubber pads for TB240 steel track unit	\$3,480



519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

# TB260

## Compact Excavator

### STANDARD EQUIPMENT

<p>Operating Weight: 12,180 lbs.          Width: 6' 6.7"          Maximum Dig Depth: 12' 9.4"          Bucket Digging Force: 12,756 lbs.          Horsepower / RPM: 47.6 / 2,400          Travel Speed: 1.7 / 3.0 mph          Primary Aux Flow: 27.0 gpm          Second Aux Flow: 11.6 gpm          Boom Swing: Left 78°/ Right 55°          Track Width: 15.7"</p> <p>Two speed travel with automatic shift down          Reinforced arm w/ Integrated thumb mount          Heavy duty dozer blade with float          Auto Idle</p>	<p>TOPS/ROPS/FOPS 4 post canopy          Color gauge panel with multi-function operator information center          Adjustable high back suspension seat          Pilot operated joystick control with control pattern change valve          Proportional slide switch control auxiliary hydraulics          EPA Final Tier 4 Turbocharged engine with DPF and engine monitoring system          Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door          Side by side radiator and hydraulic cooler          Variable Displacement axial piston pump          Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls          Primary auxiliary continuous mode and one-way mode          Safety features include: TOPS/ROPS/FOPS 4 post Canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights</p>
---	--

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB260	TB260 Equipped with ROPS/TOPS/FOPS canopy, Rubber or Steel Tracks	\$71,807
TB260A (w/Angle Blade)	TB260 Canopy (above Equipped) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$74,897
TB260L (w/ Road Liner Tracks)	TB260 Canopy (above Equipped with <b>Road Liner Tracks</b> )	\$76,957
TB260LA (w/ Angle Blade & Road Liner Tracks)	TB260 Canopy (above Equipped with <b>Road Liner Tracks</b> ) w/ <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$80,047
TB260C	TB260 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet	\$78,605
TB260CA (w/Angle Blade)	TB260 Cab (above Equipped) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$81,695
TB260CL (w/ Road Liner Tracks)	TB260 Cab (above Equipped with <b>Road Liner Tracks</b> )	\$83,755
TB260CLA (w/ Angle Blade & Road Liner Tracks)	TB260 Cab (above Equipped with <b>Road Liner Tracks</b> ) w/ <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$86,845

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB26012	12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$945
BTB26018	18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,000
BTB26024	24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,080
BTB26036	36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,340
BQC26000	Quick Coupler	\$800
BQC14512	12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$945
BQC14518	18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,000
BQC14524	24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,080
BQC14536	36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,340
BQC14536D	36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,283
BTH260I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,070

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH260K	Hydraulic Thumb (Only compatible with 18" and larger buckets)	\$1,722

Prices and specifications  
 subject to change without notice

P-5  
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA  
 Effective 1 January 2016

### STANDARD EQUIPMENT

<p>Operating Weight: 18,780 lbs.                  Width: 7' 7"                  Maximum Dig Depth: 15'                  Bucket Digging Force: 16,565 lbs.                  Net Horsepower / RPM: 69.2 / 2,000                  Travel Speed: 1.6 / 3.1 mph                  Auxiliary Flow: 26.4 gpm / 14.5 gpm                  Boom Swing: Left 70° / Right 60°                  Track Width: 17.7" Rubber / 21.7" Steel</p> <p>Two speed travel with automatic shift down                  Reinforced arm w/ Integrated thumb mount                  Heavy duty dozer blade with float                  Automatic track tensioner                  Auto Idle</p>	<p>ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet, and AM/FM/MP3 radio                  Color 5.7" gauge panel with multi-function operator information center                  10-way adjustable high back suspension seat                  Pilot operated joystick control with control pattern change valve                  EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system                  Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door                  Side by side radiator and hydraulic cooler                  Load sensing variable displacement hydraulic system                  Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch                  Primary auxiliary continuous mode and one-way mode                  Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights</p>
---	---

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB290C	TB290 Cab Equipped with Rubber or Steel Tracks	\$113,815
TB290CA (w/ Angle Blade)	TB290 Cab (above Equipped) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$119,995
TB290CL (w/ Road Liner Tracks)	TB290 Cab (above Equipped except with <b>Road Liner Tracks</b> )	\$119,779
TB290CLA (w/ Angle Blade & Road Liner Tracks)	TB290 Cab (above Equipped except with <b>Road Liner Tracks</b> ) with <b>Angle Blade</b> Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$125,959

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB07018	18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,080
BTB07024	24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,155
BTB07036	36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07000	Quick Coupler	\$1,030
BQC07018	18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,080
BQC07024	24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,155
BQC07036	36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07036D	36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,420
BTH0701	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,790

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH070K	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$2,435

# TAKEUCHI

# TB280FR

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

## Zero Swing Excavator

### STANDARD EQUIPMENT

Operating Weight: 19,077 lbs. Width: 7' 7" Maximum Dig Depth: 14' 11" Bucket Digging Force: 16,335 lbs. Horsepower / RPM: 69.2 / 2,000 Travel Speed: 1.6 / 3.1 mph Auxiliary Flow: 39 gpm / 15 gpm Boom swing: Left 30°/ Right 15° Track Width: 17.7"  Side-to-Side (STS) offset boom system Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Auto idle	ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet and AM/FM/MP3 radio Tilt-up operator's platform Color 5.7" gauge panel with multi-function operator information center 10-way adjustable high back suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable displacement axial piston main hydraulic pumps Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch Primary auxiliary continuous mode and one-way mode Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights
--	--

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB280FRC	<b>TB280FR Cab</b> Equipped with Rubber or Steel Tracks	\$117,420
TB280FRCL (w/ Road Liner Tracks)	<b>TB280FR Cab</b> Equipped with <b>Road Liner Tracks</b>	\$123,384

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BTB07018	18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,080
BTB07024	24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,155
BTB07036 *	36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07000	Quick Coupler	\$1,030
BQC07018	18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,080
BQC07024	24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,155
BQC07036 *	36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07036D *	36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,420
BTH070I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,790

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2" belt	\$91
BTH070K *	Hydraulic thumb ( Only compatible with 18" and larger buckets)	\$2,435

\* **NOTE:** The Zero Swing front radius feature is only available for the standard bucket attachment (30" or smaller)

# TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

# TB1140

SERIES 2

Excavator

### STANDARD EQUIPMENT

Operating Weight: 34,700 lbs. (Steel)	Factory installed cab with auto air conditioner/heat/defroster, AM/FM/MP3 radio, wiper
Dozer Blade Width: 8' 6"	Air suspension seat
Maximum Dig Depth: 18' 0"	Two speed travel with automatic shift down
Bucket Digging Force: 22,188 lbs.	Travel alarm
Tail Swing Radius: 6' 9"	Arm & Boom holding valve with lift alarm
Horsepower / RPM: 103.3 / 2,000	Control pattern selector valve
EPA Interim Tier 4 Compliant	Pilot operated joystick controls with safety lock out
Travel Speed: 1.9 / 3.3 mph	Wrap around counterweight
Auxiliary Flow: (Primary) 59 gpm	Adjustable air suspension seat with retractable seat belt
Auxiliary Flow: (Secondary) 14.5 gpm	Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm
Boom swing: Left 77° / Right 53°	Electrohydraulic push button controls of auxiliary hydraulic circuit (Primary Only)
24" Wide Steel Tracks	Proportional thumb control of both auxiliary hydraulic circuits
Optional: 20" Rubber Track	Variable displacement axial piston main hydraulic pumps
Optional: 20" Road Liner style tracks	LCD gauge panel with multi-function operator information center
	Heavy duty dozer blade with Float
	Accumulator

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB1140	TB1140 Equipped with CAB, Rubber or Steel Tracks, Dozer blade with float, Auto Air Conditioner/Heat, Defroster, Windshield wiper and washer, Control pattern selector valve, Travel alarm, Cab light, Auxiliary hydraulics (primary and secondary), Slide back front window, AM/FM/MP3 radio, Air Suspension seat, Engine monitoring system	\$160,395
TB1140CL (w/ Road Liner Tracks)	TB1140 Cab (above Equipped except with <b>Road Liner Tracks</b> )	\$169,343

### BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

### ATTACHMENTS

BMC1140	Mechanical Coupler: Pin Grabber type with Pins (700 lbs)	\$5,130
BTB114018	18" Pin-On Bucket (Capacity 0.41) (875 lbs)	\$2,745
BTB114024	24" Pin-On Bucket (Capacity 0.57) (1025 lbs)	\$2,825
BTB114030	30" Pin-On Bucket (Capacity 0.73) (1110 lbs)	\$3,385
BTB114036	36" Pin-On Bucket (Capacity 0.89) (1295 lbs)	\$3,660
BTB114042D	42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs)	\$2,708
BTB114048D	48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs)	\$2,915
BTB114054D	54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs)	\$3,130
BTB114060D	60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs)	\$3,335
BTH1140I	INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs)	\$7,765
BTH1140LI	INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler)	\$7,765

### FIELD INSTALLED OPTIONS

K1573400001	3" Retractable seat belt in lieu of standard 2"	\$123
BTH1140K	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs)	\$7,305
BTH1140LK	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler)	\$7,305
TB1140BKTPINS	Bucket Pin Kit (includes Hardware)	\$482



# TL8

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 8,345 lbs.	ROPS/FOPS tilt-up operators compartment w/ RH/LH rearview mirrors
Overall Width Without Bucket:(12"/15" Tracks) 62"/ 65"	Back-up alarm, Top and rear windows
Tipping Load (SAE 732) 6,020 lbs.	Automatic fuel bleed system
Rated Operating Capacity (ROC)(SAE J818): 2,105 lbs	Pilot operated joystick controls
Bucket Digging Force: 6,834 lbs.	Universal quick attach mounting bracket
Horsepower / RPM: 74.3 / 2,600	Six-way adjustable suspension seat with retractable seatbel
Travel Speed: 4.5 / 6.8 mph	One and two way auxiliary hydraulics
Auxiliary Flow: 18.4 gpm	Electronic engine monitoring system
Ground Pressure: 4.4 psi	Electrohydraulic push button controls of auxiliary hydraulic circuit
Maximum Lift Height to Bucket Pin: 9' 11"	Proportional slide switch control auxiliary hydraulics with detent function
Reach Fully Raised: 2' 4.7"	Hydraulic self-leveling bucket
Canopy/Cab height: 6' 11.9" / 7' 4"	Flat face, pressure releasing Hydraulic Couplers
	Standard 14-pin connector with push button contro
	Dual element air cleaner with standard pre-cleaner
EPA Final Tier 4 Turbocharged Engine with DPF	Push button boom float with detent
	Foot Throttle

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL8RW	TL8 with ROPS/FOPS Canopy, 15" Rubber tracks	\$53,303
TL8RWP (w/ PC)	TL8RW (above Equipped) with <b>Pattern Control*</b>	\$54,281
TL8CRW	TL8 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15" Rubber Tracks, Hydraulic quick attach, Roll up door	\$59,483
TL8CRWP (w/ PC)	TL8CRW (above Equipped) with <b>Pattern Control*</b>	\$60,461
<hr/>		
TL8RN	TL8 with ROPS/FOPS Canopy, 12" Rubber tracks	\$52,816
TL8RNP (w/ PC)	TL8RN (above Equipped) with <b>Pattern Control*</b>	\$53,795
TL8CRN	TL8 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 12" Rubber Tracks, Hydraulic quick attach, Roll up door	\$58,996
TL8CRNP (w/ PC)	TL8CRN (above Equipped) with <b>Pattern Control*</b>	\$59,975

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS

NOTE: 67" and 76" buckets work with both 12" / 15" Track's

BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	\$1,570
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	\$1,465
ABLU-72S-057	72" Low Profile Bucket - Smooth with Bolt on Cutting Edge	\$1,612
ABLU-72T-057	72" Low Profile Bucket - Tooth	\$1,523
BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,040
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$1,895
BPL1200	7' six way dozer blade	\$6,325
BTLPF48	HD 48" pallet forks and frame	\$1,185
K288547011	Radio kit installed (AM/FM/MP3)	\$500
K48834204I	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
K48834204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28833001	Counter Weight Kit TL8 (350 lbs)(Increase ROC to 2,323 lb)	\$900
K488710000	H pattern fixed control kit for TL8	\$353
K48837001	TL8 hydraulic quick attach coupler kit (for Canopy unit)	\$1,560
K28854701	Radio kit (AM/FM/MP3)	\$421
1903908050	Active Power Control Kit (Field Kit)	\$300



# TL8

## Track Loader

### HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

#### STANDARD EQUIPMENT

Operating Weight: 8,620 lbs.	ROPS/FOPS tilt-up operators compartment w/ RH/LH rearview mirrors
Overall Width Without Bucket (w/ 15" Tracks): 65"	Back-up alarm, Top and rear windows
Tipping Load (SAE 732): 6,020 lbs.	Automatic fuel bleed system
Rated Operating Capacity (ROC)(SAE J818): 2,105 lbs	Pilot operated joystick controls
Bucket Digging Force: 6,834 lbs.	Universal quick attach mounting bracket
Horsepower / RPM: 74.3 / 2,600	Six-way adjustable suspension seat with retractable seatbelt
Travel Speed: 4.5 / 6.8 mph	One and two way auxiliary hydraulics
Auxiliary Flow: 18.4 gpm STD / 33 gpm HF	Electronic engine monitoring system
Ground Pressure: 4.5 psi	Electrohydraulic push button controls of auxiliary hydraulic circuit
Maximum Lift Height to Bucket Pin: 9' 11"	Proportional slide switch control auxiliary hydraulics with detent function
Reach Fully Raised: 2' 4.7"	Hydraulic self-leveling bucket
Cab height: 7' 4"	1/2" Flat face, pressure relieving Hydraulic Couplers
1/2" Lexan roll up door	Standard 14-pin connector with push button control
EPA Final Tier 4 turbocharged engine with DPF	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent
	Foot throttle

#### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL8CRWH	TL8 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15" Rubber Tracks, Hydraulic quick attach, Lexan Roll up door and HIGH FLOW auxiliary hydraulics (33 gpm)	\$62,315
TL8CRWHP (w/ PC)	TL8CRW (above Equipped) with <b>Pattern Control*</b>	\$63,294

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC requires a minimum of 90 days delivery time for factory order

#### ATTACHMENTS

BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	\$1,570
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	\$1,465
ABLU-72S-057	72" Low Profile Bucket - Smooth with Bolt on Cutting Edge	\$1,612
ABLU-72T-057	72" Low Profile Bucket -Tooth	\$1,523
BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,040
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$1,895
BPL1200	7' six way dozer blade	\$6,325
BTLPF48	HD 48" pallet forks and frame	\$1,185
K288547011	Radio kit installed (AM/FM/MP3)	\$500
K488342041	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

#### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
K48834204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28833001	Counter Weight Kit TL8 (350 lbs)(Increase ROC to 2,323 lb)	\$900
K488710000	H pattern fixed control kit for TL8	\$353
K28854701	Radio kit (AM/FM/MP3)	\$421
1903908050	Active Power Control Kit (Field Kit)	\$300



# TL10

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 10,318 lbs.	ROPS/FOPS tilt-up operators compartment with foot throttle
Overall Width Without Bucket: 69.7"	Back-up alarm
Tipping Load (SAE 732) 6,867 lbs.	Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,403 lbs	Automatic fuel bleed system
Bucket Digging Force: 7,400 lbs.	Pilot operated joystick controls
Horsepower / RPM: 90.7 / 2,400	Universal quick attach mounting bracket
Travel Speed: 4.6 / 7.2	Six-way adjustable suspension seat with retractable seatbelt
Auxiliary Flow: 20 gpm	One and two way auxiliary hydraulics
Ground Pressure: 4.4 PSI	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 10' 3"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 34.4"	Proportional slide switch control auxiliary hydraulics with detent function
Canopy/Cab height: 7' 5.4"	Hydraulic self-leveling bucket
Front & rear working lights	Flat face, pressure relieving Hydraulic Couplers
Level 2 FOPS operator protection	Standard 14-pin connector with push button control
Selectable Hydraulic Modes	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL10R	TL10 with ROPS/FOPS Canopy, 17.7" Rubber tracks	\$64,025
TL10RR (w/ RC)	TL10R (above Equipped) with <b>Ride Control*</b>	\$64,725
TL10RP (w/ PC)	TL10R (above Equipped) with <b>Pattern Control*</b>	\$64,975
TL10RRP (w/ RC & PC)	TL10R (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	\$65,675

TL10CR	TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door	\$70,495
TL10CRR (w/ RC)	TL10CR (above Equipped) with <b>Ride Control*</b>	\$71,195
TL10CRP (w/ PC)	TL10CR (above Equipped) with <b>Pattern Control*</b>	\$71,445
TL10CRRP (w/ RC & PC)	TL10CR (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	\$72,145

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,040
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$1,895
BPL1200	7' six way dozer blade	\$6,325
BTLPF48	HD 48" pallet forks and frame	\$1,185
K288547011	Radio kit installed (AM/FM/MP3)	\$500
K288542041	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

### FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91
K28854204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28854701	Radio kit (AM/FM/MP3)	\$421
K28839903	H pattern fixed control kit for TL10/TL12	\$375
K38847001	TL10 hydraulic quick attach coupler kit (for Canopy unit)	\$1,630
K28853001	Counterweight kit for TL10 (575 lbs) - Increase in ROC to 2,723 lbs	\$1,550
1903908060	Active Power Control Kit (Field Kit)	\$300
K388440000	TL10 cold weather panel kit	\$120

Prices and specifications  
subject to change without notice

P-10-A  
Prices are in US Dollar

Prices are F.O.B. Pendergrass,GA  
Effective 1 January 2016



# TL10

## Track Loader HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 10,516 lbs.	ROPS/FOPS tilt-up operators compartment with foot throttle
Overall Width Without Bucket: 69.7"	Back-up alarm
Tipping Load (SAE 732) 6,867 lbs.	Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,403 lbs	Automatic fuel bleed system
Bucket Digging Force: 7,400 lbs.	Pilot operated joystick controls
Horsepower / RPM: 90.7 / 2,400	Universal quick attach mounting bracket
Travel Speed: 4.6 / 7.2	Six-way adjustable suspension seat with retractable seatbelt
Auxiliary Flow (SP1): 20 gpm STD / 36 gpm HF	One and two way auxiliary hydraulics
Auxiliary Flow (SP2): 17 gpm	Electronic engine monitoring system
Ground Pressure: 4.4 PSI	Electrohydraulic push button controls of auxiliary hydraulic circuit
Maximum Lift Height to Bucket Pin: 10' 3"	Proportional slide switch control auxiliary hydraulics with detent function
Reach Fully Raised: 34.4"	Hydraulic self-leveling bucket
Canopy/Cab height: 7' 5.4"	Flat face, pressure relieving Hydraulic Couplers
Front & rear working lights	Standard 14-pin connector with push button control
Level 2 FOPS operator protection	Dual element air cleaner with standard pre-cleaner
Selectable Hydraulic Modes	Push button boom float with detent

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL10CRH	TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics w/ second auxillary line	\$73,545
TL10CRHR (w/ RC)	TL10CRH (above Equipped) with <b>Ride Control*</b>	\$74,245
TL10CRHP (w/ PC)	TL10CRH (above Equipped) with <b>Pattern Control*</b>	\$74,495
TL10CRHRP (w/ RC & PC)	TL10CRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	\$75,195

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,040
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$1,895
BPL1200	7' six way dozer blade	\$6,325
BTLPF48	HD 48" pallet forks and frame	\$1,185
K288547011	Radio kit installed (AM/FM/MP3)	\$500
K288542041	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

### FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91
K28854204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28854701	Radio kit (AM/FM/MP3)	\$421
K28839903	H pattern fixed control kit for TL10/TL12	\$375
K28853001	Counterweight kit for TL10 (575 lbs) - Increase in ROC to 2,723 lbs	\$1,550
1903908060	Active Power Control Kit (Field Kit)	\$300
K388440000	TL10 cold weather panel kit	\$120



# TL12

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 11,618 lbs.	ROPS/FOPS tilt-up operators compartment with foot throttle
Overall Width Without Bucket: 73.2"	Back-up alarm
Tipping Load (SAE 732) 8,102 lbs.	Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,833 lbs	Automatic fuel bleed system
Bucket Digging Force: 8,670 lbs.	Pilot operated joystick controls
Horsepower / RPM: 108.4 / 2,400	Universal quick attach mounting bracket
Travel Speed: 4.9 / 7.4 mph	Six-way adjustable suspension seat with retractable seatbel
Auxiliary Flow: 23 gpm	One and two way auxiliary hydraulics
Ground Pressure: 4.6 psi	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 10' 6"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 38.8"	Proportional slide switch control auxiliary hydraulics with detent function
Canopy/Cab height: 7' 7.3"	Hydraulic self-leveling bucket
Front & rear working lights	Flat face, pressure relieving Hydraulic Couplers
Level 2 FOPS operator protection	Standard 14-pin connector with push button control
Selectable Hydraulic Modes	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12R	TL12 with ROPS/FOPS Canopy, 17.7" Rubber tracks	\$76,845
TL12RR (w/ RC)	TL12R (above Equipped) with Ride Control*	\$77,545
TL12RP (w/ PC)	TL12R (above Equipped) with Pattern Control*	\$77,795
TL12RRP (w/ RC & PC)	TL12R (above Equipped) with Ride Control & Pattern Control*	\$78,495
TL12CR	TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door	\$83,395
TL12CRR (w/ RC)	TL12CR (above Equipped) with Ride Control*	\$84,095
TL12CRP (w/ PC)	TL12CR (above Equipped) with Pattern Control*	\$84,345
TL12CRRP (w/ RC & PC)	TL12CR (above Equipped) with Ride Control & Pattern Control*	\$85,045

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$2,270
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$2,095
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$2,570
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	\$2,472
BPL12008	8' six way dozer blade	\$6,500
BTLPF48	HD 48" pallet forks and frame	\$1,185
K288547011	Radio kit Installed (AM/FM/MP3)	\$500
K288542041	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

### FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91
K28854204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28854701	Radio kit (AM/FM/MP3)	\$421
K28839903	H pattern fixed control kit for TL10/TL12	\$375
K38857001	TL12 hydraulic quick attach coupler kit (for Canopy unit)	\$1,630
K28853001	Counterweight kit for TL12 (575 lbs) - Increase in ROC to 3,263 lbs	\$1,550
1903908060	Active Power Control Kit (Field Kit)	\$300
K388540000	TL12 cold weather panel kit	\$120



# TL12

## Track Loader

### HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

#### STANDARD EQUIPMENT

Operating Weight: 11,850 lbs.	ROPS/FOPS tilt-up operators compartment with foot throttle
Overall Width Without Bucket: 73.2"	Back-up alarm
Tipping Load (SAE 732) 8,102 lbs.	Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,833 lbs	Automatic fuel bleed system
Bucket Digging Force: 8,670 lbs.	Pilot operated joystick controls
Horsepower / RPM: 108.4 / 2,400	Universal quick attach mounting bracket
Travel Speed: 4.9 / 7.4 mph	Six-way adjustable suspension seat with retractable seatbelt
Auxiliary Flow (SP1): 23 gpm STD / 40 gpm HF	One and two way auxiliary hydraulics
Auxiliary Flow (SP2): 17 gpm	Electronic engine monitoring system
Ground Pressure: 4.6 psi	Electrohydraulic push button controls of auxiliary hydraulic circuit
Maximum Lift Height to Bucket Pin: 10' 6"	Proportional slide switch control auxiliary hydraulics with detent function
Reach Fully Raised: 38.8"	Hydraulic self-leveling bucket
Cab height: 7' 7.3"	Flat face, pressure relieving Hydraulic Couplers
Front & rear working lights	Standard 14-pin connector with push button control
Level 2 FOPS operator protection	Dual element air cleaner with standard pre-cleaner
Selectable Hydraulic Modes	Push button boom float with detent

#### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12CRH	TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line	\$86,395
TL12CRHR (w/ RC)	TL12CRH (above Equipped) with <b>Ride Control*</b>	\$87,095
TL12CRHP (w/ PC)	TL12CRH (above Equipped) with <b>Pattern Control*</b>	\$87,345
TL12CRHRP (w/ RC & PC)	TL12CRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	\$88,045

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

#### ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$2,270
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$2,095
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$2,570
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	\$2,472
BPL12008	8' six way dozer blade	\$6,500
BTLPF48	HD 48" pallet forks and frame	\$1,185
K288547011	Radio kit Installed (AM/FM/MP3)	\$500
K288542041	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

#### FIELD INSTALLED OPTIONS

1914199948	3" retractable seat belt in lieu of standard 2"	\$91
K28854204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28854701	Radio kit (AM/FM/MP3)	\$421
K28839903	H pattern fixed control kit for TL10/TL12	\$375
K28853001	Counterweight kit for TL12 (575 lbs) - Increase in ROC to 3,263 lbs	\$1,550
1903908060	Active Power Control Kit (Field Kit)	\$300
K388540000	TL12 cold weather panel kit	\$120



# TL12V2

## Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 12,434 lbs.	Vertical boom design
Overall Width Without Bucket: 77.2"	ROPS/FOPS tilt-up operators compartment
Tipping Load (SAE 732) 11,737 lbs.	Electric dial and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs	Back-up alarm
Bucket Digging Force: 7,884 lbs.	Top and rear window
EPA Final Tie 4 with DOC + DPF + SCR	Automatic fuel bleed system
Horsepower / RPM: 111.3 / 2,400	Pilot operated joystick controls
Travel Speed: 5.0 / 7.3 mph	Universal quick attach mounting bracket
Auxiliary Flow: 23.2 gpm	Deluxe high back suspension seat with retractable seatbelt
Ground Pressure: 4.7 psi	One and two way auxiliary hydraulics
Maximum Lift Height to Bucket Pin: 10' 10"	Electronic engine monitoring system
Reach Fully Raised: 36.4"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Canopy/Cab height: 7' 7.6"	Proportional slide switch control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
Selectable working modes	Flat face, pressure relieving hydraulic couplers
Active power control power management system	Standard 14-pin connector with push button control
	Dual element air cleaner
	Push button boom float with detent

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12V2-R	TL12V with ROPS/FOPS Canopy, 17.7" Rubber tracks	\$83,500
TL12V2-RR (w/ RC)	TL12VR (above Equipped) with Ride Control*	\$84,200
TL12V2-RP (w/ PC)	TL12VR (above Equipped) with Pattern Control*	\$84,450
TL12V2-RRP (w/ RC & PC)	TL12VR (above Equipped) with Ride Control & Pattern Control*	\$85,150

TL12V2-CR	TL12V with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, AM/FM Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door	\$90,050
TL12V2-CRR (w/ RC)	TL12VCR (above Equipped) with Ride Control*	\$90,750
TL12V2-CRP (w/ PC)	TL12VCR (above Equipped) with Pattern Control*	\$91,000
TL12V2-CRRP (w/ RC & PC)	TL12VCR (above Equipped) with Ride Control & Pattern Control*	\$91,700

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$2,270
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$2,095
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$2,570
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity	\$2,472
BPL12008	8' six way dozer blade	\$6,500
BTLPF48	HD 48" pallet forks and frame	\$1,185

### FIELD INSTALLED OPTIONS



# TL12V2

Track Loader  
HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567  
Tel:706-693-3600 Fax:706-693-3725  
www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 12,756 lbs.	Vertical boom design
Overall Width Without Bucket: 77.2"	ROPS/FOPS tilt-up operators compartment
Tipping Load (SAE 732) 11,737 lbs.	Electric dial and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs	Back-up alarm
Bucket Digging Force: 7,884 lbs.	Top and rear window
EPA Final Tie 4 with DOC + DPF + SCR	Automatic fuel bleed system
Horsepower / RPM: 111.3 / 2,400	Pilot operated joystick controls
Travel Speed: 5.0 / 7.3 mph	Universal quick attach mounting bracket
Auxiliary Flow (Std / High Flow): 23.2 gpm / 40 gpm	Deluxe high back suspension seat with retractable seatbelt
Ground Pressure: 4.7 psi	One and two way auxiliary hydraulics
Maximum Lift Height to Bucket Pin: 10' 10"	Electronic engine monitoring system
Reach Fully Raised: 36.4"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Canopy/Cab height: 7' 7.6"	Proportional slide switch control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
Selectable working modes	Flat face, pressure relieving hydraulic couplers
Active power control power management system	Standard 14-pin connector with push button control
	Dual element air cleaner
	Push button boom float with detent

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12V2-CRH	TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, AM/FM Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line	\$93,050
TL12V2-CRHR (w/ RC)	TL12VCRH (above Equipped) with <b>Ride Control*</b>	\$93,750
TL12V2-CRHP (w/ PC)	TL12VCRH (above Equipped) with <b>Pattern Control*</b>	\$94,000
TL12V2-CRHRP (w/ RC & PC)	TL12VCRH (above Equipped) with <b>Ride Control &amp; Pattern Control*</b>	\$94,700

### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

\* PC & RC requires a minimum of 90 days delivery time for factory order

### ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$2,270
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$2,095
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$2,570
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity	\$2,472
BPL12008	8' six way dozer blade	\$6,500
BTLPF48	HD 48" pallet forks and frame	\$1,185

### FIELD INSTALLED OPTIONS

# TAKEUCHI®

# TW40

## Wheel Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

### STANDARD EQUIPMENT

Operating Weight: 7,275 lbs	Back-Up Alarm
Tip Load, Straight: 5,842 lbs	Front Working Lights
Bucket breakout force: 7,126 lbs	Rear Working Lights
HP / RPM: 39.4 hp / 2,800 rpm	Inching Pedal
Travel Speed (Max): 12.4 gpm	Front Limited Slip Axle 45%
Auxiliary Flow: 10.3 gpm	Auxiliary Hydraulic Lines
Maximum Height to Bucket pin: 9' 7.7"	Replaceable Bushings
Height: (Canopy) 8' / (Cab) 8' 2"	Bucket Float
Articulation: 40 /40	Automatic Bucket Positioning
Lift Capacity @ G. L.: 5,260 lb	Heavy Duty Hydraulic SSL Style Quick Attach Coupler
Reach fully raised: 2' 8.5"	Center Pivot Steering
	Heavy Duty 31x15.5-15 Construction Tire Assembly
	Optional heated Cab features front/rear wiper and rear defrost

### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW40	TW40 with Foldable ROPS Canopy and Tires	\$55,105
TW40C	TW40 with Cab with Heat and Tires	\$59,740

### BASE MACHINE PRICE DOES NOT INCLUDE ATTACHMENTS

### ATTACHMENTS

BTW4060	60" General Purpose Bucket (0.66 cu. Yd) for TW40 with SSL Mount	\$2,300
BTW4060A	60" Bolt on Blade for BTW4060	\$282
BTW4060B	60" Tooth Bar for BTW4060 (note: not compatible with bolt on blade)	\$643

### FIELD INSTALLED OPTIONS

TWFASTERKIT	TW Series Coupler Kit	\$132
-------------	-----------------------	-------



# TW65

## Wheel Loader

### SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

#### STANDARD EQUIPMENT

<p>Operating Weight: 11,354 lbs          Tip Load, Straight: 9,171 lbs          Bucket Breakout Force: 11,600 lbs          HP / RPM: 73 / 2200          Travel Speed (Max): 12.4 mph          Auxiliary Flow: 16.4 gpm          Maximum Height to Bucket Pin: 10 ft 4.6 in          Height: 8 ft 9.8 in          Articulation: 40 /40          Lift Capacity @ G. L.: 10,319 lbs          Reach Fully Raised: 24"</p>	<p>Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost          LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities          Deluxe suspension seat          Pilot operator loader joystick control          EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system          Side by side radiator and hydraulic oil cooler          Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick          100% Front and rear differential lock          Euro style attachment mount with hydraulic coupler          Bucket float          Mechanical bucketpositioning          Safety features include: ROPS/FOPS enclosed cab, back up alarm, lights retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights, front driving lights, front and rear hazard and directional indicators)</p>
---	---

#### ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

#### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW65C2	TW65 Cab	\$83,420
TW65C2HS	TW65 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control	\$87,746
TW65C2HF	TW65 Cab, High Flow Auxiliary Hydraulics (26 gpm)	\$88,271
TW65C2HH	TW65 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control	\$92,597

**BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES**

#### TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW65TIREHD	Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,395
BTW65TIREF	Floatation Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,950

#### ATTACHMENTS

BTW5077	77" Construction Combo Bucket (1.05 cu. Yd) for TW65/TW80	\$2,520
BTW5077A	77" Bolt on Blade for BTW5077	\$370
BTW8082	81.5" General Purpose Bucket (1.3 cu. Yd) for TW80	\$2,520
BTW8082A	82" Bolt-on Blade for BTW8082	\$370
BTWPF48	48" Combo Fork Assy for all TW's (Rated 8000 lb)	\$2,300
BTWUNIADP	Combo Hitch to Universal SSL Adapter TW50/60/65/80	\$2,200

#### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
TWFASTERKIT	TW Series Coupler Kit	\$132



# TW80

## Wheel Loader

### SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

#### STANDARD EQUIPMENT

<p>Operating Weight: 12,700 lbs          Tip Load, Straight: 10,065 lbs          Bucket Breakout Force: 12,287 lbs          HP / RPM: 73 / 2200          Travel Speed (Max): 12.4 mph          Auxiliary Flow: 16.4 gpm          Maximum Height to Bucket Pin: 11 ft 1 in          Height: 8 ft 11.5 in          Articulation: 40 /40          Lift Capacity @ G. L.: 12,287 lbs          Reach Fully Raised: 29"</p>	<p>Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost          LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities          Deluxe suspension seat          Pilot operator loader joystick control          EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system          Side by side radiator and hydraulic oil cooler          Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick          100% Front and rear differential lock          Euro style attachment mount with hydraulic coupler          Bucket float          Mechanical bucket positioning          Safety features include: ROPS/FOPS enclosed cab, back up alarm, lights retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights, front driving lights, front and rear hazard and directional indicators)</p>
---	--

#### ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

#### BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW80C2	TW80 Cab	\$92,690
TW80C2HS	TW80 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control	\$97,016
TW80C2HF	TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm)	\$97,541
TW80C2HH	TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control	\$101,867

#### BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

#### TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW65TIREHD	Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,395
BTW65TIREF	Floatation Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,950

#### ATTACHMENTS

BTW8082	81.5" General Purpose Bucket (1.3 cu. Yd) for TW80	\$2,520
BTW8082A	82" Bolt-on Blade for BTW8082	\$370
BTWPF48	48" Combo Fork Assy for all TW's (Rated 8000 lb)	\$2,300
BTWUNIADP	Combo Hitch to Universal SSL Adapter TW50/60/65/80	\$2,200

#### FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
TWFASTERKIT	TW Series Coupler Kit	\$132



# P3-Power Protection Plan

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

### Excavators

Model			TB 108	TB 216	TB230	TB240
2YR/2000HR	Full Machine	Item #	n/a	n/a	n/a	n/a
2YR/2000HR	Full Machine	List	std	std	std	std
3YR/3000HR	Power train	Item_Number	EW108P32	EW216P31	EW230P31	EW240P31
3YR/3000HR	Power train	List	\$478	\$628	\$844	\$1,157
3YR/3000HR	Power Train & Hydraulic	Item_Number	EW108PH32	EW216PH31	EW230PH31	EW240PH31
3YR/3000HR	Power Train & Hydraulic	List	\$797	\$1,047	\$1,407	\$1,928
3YR/3000HR	Full Machine	Item_Number	EW108FM32	EW216FM31	EW230FM31	EW240FM31
3YR/3000HR	Full Machine	List	\$996	\$1,308	\$1,759	\$2,410
4YR/4000HR	Power train	Item_Number	EW108P42	EW216P41	EW230P41	EW240P41
4YR/4000HR	Power train	List	\$1,116	\$1,465	\$1,970	\$2,699
4YR/4000HR	Power Train & Hydraulic	Item_Number	EW108PH42	EW216PH41	EW230PH41	EW240PH41
4YR/4000HR	Power Train & Hydraulic	List	\$1,714	\$2,250	\$3,025	\$4,145
5YR/5000HR	Power train	Item_Number	EW108P52	EW216P51	EW230P51	EW240P51
5YR/5000HR	Power train	List	\$1,275	\$1,675	\$2,251	\$3,085
5YR/5000HR	Power Train & Hydraulic	Item_Number	EW108PH52	EW216PH51	EW230PH51	EW240PH51
5YR/5000HR	Power Train & Hydraulic	List	\$1,953	\$2,564	\$3,447	\$4,723

			TB260	TB290	TB280FR	TB 1140
2YR/2000HR	Full Machine	Item #	n/a	n/a	n/a	n/a
2YR/2000HR	Full Machine	List	std	std	std	std
3YR/3000HR	Power train	Item #	EW260P31	EW290P31	EW280P31	EW1140P32
3YR/3000HR	Power train	List	\$1,572	\$2,147	\$2,276	\$3,045
3YR/3000HR	Power Train & Hyd	Item #	EW260PH31	EW290PH31	EW280PH31	EW1140PH32
3YR/3000HR	Power Train & Hyd	List	\$2,621	\$3,578	\$3,794	\$5,075
3YR/3000HR	Full Machine	Item #	EW260FM31	EW290FM31	EW280FM31	EW1140FM32
3YR/3000HR	Full Machine	List	\$3,276	\$4,472	\$4,742	\$6,344
4YR/4000HR	Power train	Item #	EW260P41	EW290P41	EW280P41	EW1140P42
4YR/4000HR	Power train	List	\$3,669	\$5,009	\$5,311	\$7,105
4YR/4000HR	Power Train & Hyd	Item #	EW260PH41	EW290PH41	EW280PH41	EW1140PH42
4YR/4000HR	Power Train & Hyd	List	\$5,635	\$7,692	\$8,157	\$10,912
5YR/5000HR	Power train	Item #	EW260P51	EW290P51	EW280P51	EW1140P52
5YR/5000HR	Power train	List	\$4,193	\$5,724	\$6,070	\$8,120
5YR/5000HR	Power Train & Hyd	Item #	EW260PH51	EW290PH51	EW280PH51	EW1140PH52
5YR/5000HR	Power Train & Hyd	List	\$6,421	\$8,765	\$9,295	\$12,434

For pricing on older models, please visit [www.takeuchi-us.com](http://www.takeuchi-us.com) under the P3 section



# P3-Power Protection Plan

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

### Track Loaders

			TL8	TL10	TL10H	TL12	TL12H
2YR/2000HR	Full Machine	Item_Number	n/a	n/a	n/a	n/a	n/a
2YR/2000HR	Full Machine	List	std	std	std	std	std
3YR/3000HR	Power train	Item_Number	EWL8P31	EWL10P31	EWL10HP31	EWL12P31	EWL12HP31
3YR/3000HR	Power train	List	\$1,033	\$1,343	\$1,473	\$1,600	\$1,747
3YR/3000HR	Power Train & Hydraulic	Item_Number	EWL8PH31	EWL10PH31	EWL10HPH31	EWL12PH31	EWL12HPH31
3YR/3000HR	Power Train & Hydraulic	List	\$1,722	\$2,238	\$2,454	\$2,667	\$2,912
3YR/3000HR	Full Machine	Item_Number	EWL8FM31	EWL10FM31	EWL10HFM31	EWL12FM31	EWL12HFM31
3YR/3000HR	Full Machine	List	\$2,153	\$2,798	\$3,068	\$3,333	\$3,640
4YR/4000HR	Power train	Item_Number	EWL8P41	EWL10P41	EWL10HP41	EWL12P41	EWL12HP41
4YR/4000HR	Power train	List	\$2,411	\$3,133	\$3,436	\$3,733	\$4,077
4YR/4000HR	Power Train & Hydraulic	Item_Number	EWL8PH41	EWL10PH41	EWL10HPH41	EWL12PH41	EWL12HPH41
4YR/4000HR	Power Train & Hydraulic	List	\$3,703	\$4,812	\$5,277	\$5,733	\$6,261
5YR/5000HR	Power train	Item_Number	EWL8P51	EWL10P51	EWL10HP51	EWL12P51	EWL12HP51
5YR/5000HR	Power train	List	\$2,756	\$3,581	\$3,927	\$4,266	\$4,659
5YR/5000HR	Power Train & Hydraulic	Item_Number	EWL8PH51	EWL10PH51	EWL10HPH51	EWL12PH51	EWL12HPH51
5YR/5000HR	Power Train & Hydraulic	List	\$4,219	\$5,483	\$6,013	\$6,533	\$7,134

For pricing on older models, please visit [www.takeuchi-us.com](http://www.takeuchi-us.com) under the P3 section



# P3-Power Protection Plan

519 Bonnie Valentine Way, Pendergrass, GA 30567  
 Tel:706-693-3600 Fax:706-693-3725  
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

### Wheel Loaders

			TW 40	TW 65	TW80
2YR/2000HR	Full Machine	Item_Number	n/a	n/a	n/a
2YR/2000HR	Full Machine	List	std	std	std
3YR/3000HR	Power train	Item_Number	EW40P32	EW65P32	EW80P32
3YR/3000HR	Power train	List	\$1,068	\$1,483	\$1,687
3YR/3000HR	Power Train & Hydraulic	Item_Number	EW40PH32	EW65PH32	EW80PH32
3YR/3000HR	Power Train & Hydraulic	List	\$1,780	\$2,471	\$2,829
3YR/3000HR	Full Machine	Item_Number	EW40FM32	EW65FM32	EW80FM32
3YR/3000HR	Full Machine	List	\$2,226	\$3,089	\$3,536
4YR/4000HR	Power train	Item_Number	EW40P42	EW65P42	EW80P42
4YR/4000HR	Power train	List	\$2,493	\$3,459	\$3,960
4YR/4000HR	Power Train & Hydraulic	Item_Number	EW40PH42	EW65PH42	EW80PH42
4YR/4000HR	Power Train & Hydraulic	List	\$3,828	\$5,313	\$6,082
5YR/5000HR	Power train	Item_Number	EW40P52	EW65P52	EW80P52
5YR/5000HR	Power train	List	\$2,849	\$3,954	\$4,526
5YR/5000HR	Power Train & Hydraulic	Item_Number	EW40PH52	EW65PH52	EW80PH52
5YR/5000HR	Power Train & Hydraulic	List	\$4,362	\$6,054	\$6,931

For pricing on older models, please visit [www.takeuchi-us.com](http://www.takeuchi-us.com) under the P3 section