

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30587
 Tel. 706-693-3600 Fax. 706-693-3722
 www.takeuchi-us.com

TB210R

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 2,370 lbs. Width: 29.5" / 40.2" Maximum Dig Depth: 5' 9.1" Bucket Digging Force: 2,518 lbs. Horsepower / RPM: 11.7 / 2,200 Travel Speed: 1.2 / 2.3 mph Auxiliary Flow: 5.8 gpm Boom swing: Left 85° / Right 85° 7.1" wide rubber tracks	ROPS/TOPS 2 post foldable canopy Hydraulically retractable track frame Adjustable width dozer blade with 2 pin-on extensions Pilot operated joystick controls with safety lock out Control pattern change valve Two-way auxiliary hydraulic circuit routed to the end of the arm Adjustable seat with 2" retractable seat belt Two speed travel Travel alarm Boom mounted work light Horn Cast iron, wrap around counterweight
---	---

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB210R	TB210R Equipped with ROPS/TOPS 2-post foldable canopy, Rubber tracks, Travel alarm, Auxiliary hydraulics	\$24,750

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB00708	8" Bucket with teeth, .8 cu. ft. capacity	\$360
BTB00712	12" Bucket with teeth, 1.1 cu. ft. capacity	\$380

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

TB216

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 3,902 lbs.	ROPS/TOPS/FOPS 4 post canopy
Width: 38.6" / 51.2"	LCD gauge panel with multi-functional operator information center
Maximum Dig Depth: 7' 9.1"	Hydraulically retractable track frame
Bucket Digging Force: 4,250 lbs.	Travel alarm
Horsepower / RPM: 15 / 2,400	Two-speed travel with automatic down shift
Travel Speed: 1.4 / 2.6 mph	Control pattern selector valve
Auxiliary Flow: 8.9 gpm	Pilot operated joystick controls with safety lock out
Boom swing: Left 80°/ Right 50°	Cast iron, wrap around counterweight
9" wide rubber tracks	Adjustable suspension seat with 2" retractable seat belt
Long Arm w/ integrated thumb mount	Two-way auxiliary hydraulic circuit routed to the end of the arm
	Variable displacement axial piston main hydraulic pumps
	Adjustable width dozer blade
	Electronic engine monitoring system

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB216	TB216 Equipped with ROPS/TOPS/FOPS canopy, Rubber tracks	\$32,526

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB01608	8" Pin-On Bucket with teeth, 1.1 cu. ft. capacity	\$465
BTB01612	12" Pin-On Bucket with teeth, 1.5 cu. ft. capacity	\$480
BTB01618	18" Pin-On Bucket with teeth, 2.4 cu. ft. capacity	\$557
BTB01624	24" Pin-On Bucket with teeth, 3.2 cu. ft. capacity	\$650
BQC01600	Quick Coupler	\$785
BQC01612	12" Quick Coupler Bucket with teeth, 1.5 cu. ft. capacity	\$480
BQC01618	18" Quick Coupler Bucket with teeth, 2.4 cu. ft. capacity	\$557
BQC01624	24" Quick Coupler Bucket with teeth, 3.2 cu. ft. capacity	\$650
BQC01624D	24" Quick Coupler Ditch Bucket, 3.0 cu. ft. capacity	\$882
BTH216I	INSTALLED Hydraulic thumb (Only compatible w/ 12" or larger Buckets)	\$2,025

FIELD INSTALLED OPTIONS

1914199048	3" Non-retractable seat belt in lieu of standard 2"	\$73
BTH216K	Hydraulic thumb (Only compatible with 12" and larger buckets)	\$1,680

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-us.com

TB230

Compact Excavator

STANDARD EQUIPMENT

<p>Operating Weight: 6,607 lbs. Width: 4' 9" Maximum Dig Depth: 10' 2" Bucket Digging Force: 6,471 lbs. Horsepower / RPM: 24.4 / 2,400 Travel Speed: 1.7 / 3.0 mph Auxiliary Flow: 13.4 gpm Boom Swing: Left 80° / Right 60° Track Width: 11.8"</p> <p>Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float</p>	<p>TOPS/ROPS/FOPS 4 post canopy Color gauge panel with multi-function operator information center High back adjustable suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 compliant engine with engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door High capacity radiator and hydraulic oil cooler Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights Variable displacement axial piston pump Auto Idle</p>
--	---

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB230	TB230 Canopy Equipped with Rubber Tracks	\$42,127
TB230A (w/Angle Blade)	TB230 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$44,960

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB12512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$650
BTB12518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$675
BTB12524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12500	Quick Coupler	\$785
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$650
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$675
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$675
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,015
BTH125I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$1,920

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH125K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$1,575
1914053691A	Bolt on rubber pads for TB230 steel track unit	\$2,848

Prices and specifications
 subject to change without notice

P-3
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2016

TAKEUCHI

519 Bonnie Valentine Way Pendergrass, GA 30567
 Tel 706-693-3600 Fax 706-693-3725
 www.takeuchi-us.com

TB240

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 8,289 lbs. Width: 5' 8.5" Maximum Dig Depth: 11' 6" Bucket Digging Force: 9,959 lbs. Horsepower / RPM: 35.8 / 2,200 Travel Speed: 1.7 / 3.0 mph Auxiliary Flow: 17.1 gpm Boom Swing: Left 76° / Right 58° Track width: 13.8" Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float	TOPS/ROPS/FOPS 4 post canopy Color gauge panel with multi-function operator information center High back adjustable suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 compliant engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side industrial type radiator and hydraulic oil cooler Primary 2-way auxiliary hydraulic circuit w/adjustable flow control system, proportional slide switch, one-way mode and continuous detent mode Safety features include: TOPS/ROPS/FOPS 4 post canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights Variable displacement axial piston pump Auto Idle
---	---

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB240	TB240 Canopy Equipped with Rubber or Steel Tracks	\$54,343
TB240A (w/Angle Blade)	TB240 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$57,433
TB240C	TB240 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/Mp3 radio, 5.7" color monitor, 12v power outlet	\$61,903
TB240CA (w/ Angle Blade)	TB240 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$64,993

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB13512	12" Pin-On Bucket with teeth, 1.9 cu. ft. capacity	\$650
BTB13518	18" Pin-On Bucket with teeth, 2.7 cu. ft. capacity	\$675
BTB13524	24" Pin-On Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC13500	Quick Coupler	\$785
BQC12512	12" Quick Coupler Bucket with teeth, 1.9 cu. ft. capacity	\$650
BQC12513	13" Quick Coupler Bucket with teeth, 2.0 cu. ft. capacity	\$675
BQC12518	18" Quick Coupler Bucket with teeth, 2.7 cu. ft. capacity	\$675
BQC12524	24" Quick Coupler Bucket with teeth, 3.9 cu. ft. capacity	\$835
BQC12536D	36" Quick Coupler Ditch Bucket, 5.8 cu. ft. capacity	\$1,015
BTH135I	INSTALLED Hydraulic thumb (Only compatible w/ 13" or larger Buckets)	\$1,920

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH135K	Hydraulic thumb (Only compatible with 13" and larger buckets)	\$1,575
1914054391A	Bolt on rubber pads for TB240 steel track unit	\$3,480

Prices and specifications
subject to change without notice

P-4
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2016

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

TB260

Compact Excavator

STANDARD EQUIPMENT

Operating Weight: 12,160 lbs.
Width: 6' 6.7"
Maximum Dig Depth: 12' 9.4"
Bucket Digging Force: 12,756 lbs.
Horsepower / RPM: 47.6 / 2,400
Travel Speed: 1.7 / 3.0 mph
Primary Aux Flow: 27.0 gpm
Second Aux Flow: 11.6 gpm
Boom Swing: Left 78° / Right 55°
Track Width: 15.7"

TOPS/ROPS/FOPS 4 post canopy
Color gauge panel with multi-function operator information center
Adjustable high back suspension seat
Pilot operated joystick control with control pattern change valve
Proportional slide switch control auxiliary hydraulics
EPA Final Tier 4 Turbocharged engine with DPF and engine monitoring system
Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
Side by side radiator and hydraulic cooler
Variable Displacement axial piston pump
Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch controls
Primary auxiliary continuous mode and one-way mode
Safety features include: TOPS/ROPS/FOPS 4 post Canopy, travel alarm, retractable seat belt, control lockout, pilot accumulator, mirrors and lights

Two speed travel with automatic shift down
Reinforced arm w/ Integrated thumb mount
Heavy duty dozer blade with float
Auto idle

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB260	TB260 Equipped with ROPS/TOPS/FOPS canopy, Rubber or Steel Tracks	\$71,807
TB260A (w/Angle Blade)	TB260 Canopy (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$74,897
TB260L (w/ Road Liner Tracks)	TB260 Canopy (above Equipped with Road Liner Tracks)	\$76,957
TB260LA (w/ Angle Blade & Road Liner Tracks)	TB260 Canopy (above Equipped with Road Liner Tracks) w/ Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$80,047
TB260C	TB260 Cab Equipped with Rubber or Steel Tracks TOPS/ROPS/FOPS enclosed cab with air conditioner/heater/defrost, slide back window with removable lower section, windshield wiper and washer, skylight with sunshade, AM/FM/mp3 radio, 5.7" color monitor, 12v power outlet	\$78,605
TB260CA (w/Angle Blade)	TB260 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$81,695
TB260CL (w/ Road Liner Tracks)	TB260 Cab (above Equipped with Road Liner Tracks)	\$83,755
TB260CLA (w/ Angle Blade & Road Liner Tracks)	TB260 Cab (above Equipped with Road Liner Tracks) w/ Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$86,845

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

8TB26012	12" Pin-On Bucket with Teeth, 2.6 cu. ft. capacity	\$945
8TB26018	18" Pin-On Bucket with Teeth, 3.7 cu. ft. capacity	\$1,000
8TB26024	24" Pin-On Bucket with Teeth, 5.1 cu. ft. capacity	\$1,080
8TB26036	36" Pin-On Bucket with Teeth, 7.6 cu. ft. capacity	\$1,340
BQC28000	Quick Coupler	\$800
BQC14512	12" Quick Coupler Bucket with Teeth, 2.8 cu. ft. capacity	\$945
BQC14518	18" Quick Coupler Bucket with Teeth, 4.2 cu. ft. capacity	\$1,000
BQC14524	24" Quick Coupler Bucket with Teeth, 5.6 cu. ft. capacity	\$1,080
BQC14536	36" Quick Coupler Bucket with Teeth, 8.3 cu. ft. capacity	\$1,340
BQC14536D	36" Quick Coupler Ditch Bucket, 7.4 cu. ft. capacity	\$1,283
8TH260I	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,070

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH260K	Hydraulic Thumb (Only compatible with 18" and larger buckets)	\$1,722

Prices and specifications
subject to change without notice

P-5
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2016

TAKEUCHI

518 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-us.com

TB290

Excavator

STANDARD EQUIPMENT

Operating Weight: 18,780 lbs.
 Width: 7' 7"
 Maximum Dig Depth: 15'
 Bucket Digging Force: 16,565 lbs.
 Net Horsepower / RPM: 69.2 / 2,000
 Travel Speed: 1.6 / 3.1 mph
 Auxiliary Flow: 26.4 gpm / 14.5 gpm
 Boom Swing: Left 70° / Right 60°
 Track Width: 17.7" Rubber / 21.7" Steel

Two speed travel with automatic shift down
 Reinforced arm w/ integrated thumb mount
 Heavy duty dozer blade with float
 Automatic track tensioner
 Auto Idle

ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper,
 12v power outlet, and AM/FM/MP3 radio
 Color 5 7" gauge panel with multi-function operator information center
 10-way adjustable high back suspension seat
 Pilot operated joystick control with control pattern change valve
 EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system
 Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door
 Side by side radiator and hydraulic cooler
 Load sensing variable displacement hydraulic system
 Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow
 control system and proportional slide switch
 Primary auxiliary continuous mode and one-way mode
 Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade,
 travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding
 valve with lift alarm, mirrors and lights

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB290C	TB290 Cab Equipped with Rubber or Steel Tracks	\$113,815
TB290CA (w/ Angle Blade)	TB290 Cab (above Equipped) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$119,995
TB290CL (w/ Road Liner Tracks)	TB290 Cab (above Equipped except with Road Liner Tracks)	\$119,779
TB290CLA (w/ Angle Blade & Road Liner Tracks)	TB290 Cab (above Equipped except with Road Liner Tracks) with Angle Blade Angle Blade features 25 degree left and right angle, cylinder protective guards, replaceable bolt-on cutting edge	\$125,959

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB07018	18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,080
BTB07024	24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,155
BTB07036	36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07000	Quick Coupler	\$1,030
BQC07018	18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,080
BQC07024	24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,155
BQC07036	36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07036D	36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,420
BTH0701	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,790

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
BTH070K	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$2,435

TAKEUCHI

TB280FR

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-usa.com

Zero Swing Excavator

STANDARD EQUIPMENT

<p>Operating Weight: 19,077 lbs. Width: 7' 7" Maximum Dig Depth: 14' 11" Bucket Digging Force: 16,335 lbs. Horsepower / RPM: 69.2 / 2,000 Travel Speed: 1.6 / 3.1 mph Auxiliary Flow: 39 gpm / 15 gpm Boom swing: Left 30° / Right 15° Track Width: 17.7"</p> <p>Side-to-Side (STS) offset boom system Two speed travel with automatic shift down Reinforced arm w/ Integrated thumb mount Heavy duty dozer blade with float Auto Idle</p>	<p>ROPS/FOPS enclosed cab w/ air conditioner/heat, windshield wiper, 12v power outlet and AM/FM/MP3 radio Tilt-up operator's platform Color 5.7" gauge panel with multi-function operator information center 10-way adjustable high back suspension seat Pilot operated joystick control with control pattern change valve EPA Final Tier 4 turbocharged engine with DPF and engine monitoring system Self bleeding fuel system with ground level fuel fill, sight gauge and lockable door Side by side radiator and hydraulic cooler Variable displacement axial piston main hydraulic pumps Primary and secondary 2-way auxiliary hydraulic circuits w/adjustable flow control system and proportional slide switch Primary auxiliary continuous mode and one-way mode Safety features include: ROPS/FOPS enclosed cab, large skylight with sun shade, travel alarm, retractable seat belt, control lockout, pilot accumulator, boom holding valve with lift alarm, mirrors and lights</p>
--	---

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB280FRC	TB280FR Cab Equipped with Rubber or Steel Tracks	\$117,420
TB280FRCL (w/ Road Liner Tracks)	TB280FR Cab Equipped with Road Liner Tracks	\$123,384

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BTB07018	18" Pin-On Bucket with teeth, 5.6 cu. ft. capacity	\$1,080
BTB07024	24" Pin-On Bucket with teeth, 7.8 cu. ft. capacity	\$1,155
BTB07036 *	36" Pin-On Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07000	Quick Coupler	\$1,030
BQC07018	18" Quick Coupler Bucket with teeth, 6.2 cu. ft. capacity	\$1,080
BQC07024	24" Quick Coupler Bucket with teeth, 8.6 cu. ft. capacity	\$1,155
BQC07036 *	36" Quick Coupler Bucket with teeth, 12.2 cu. ft. capacity	\$1,445
BQC07036D *	36" Quick Coupler Ditch Bucket 11.5 cu. ft. capacity	\$1,420
BTH0701	INSTALLED Hydraulic thumb (Only compatible w/ 18" or larger Buckets)	\$2,790

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2" belt	\$91
BTH070K *	Hydraulic thumb (Only compatible with 18" and larger buckets)	\$2,435

* NOTE: The Zero Swing front radius feature is only available for the standard bucket attachment (30" or smaller)

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3800 Fax: 706-693-3725
 www.takeuchi-usa.com

TB1140

SERIES 2

Excavator

STANDARD EQUIPMENT

Operating Weight: 34,700 lbs. (Steel)	Factory installed cab with auto air conditioner/heat/defroster, AM/FM/MP3 radio, wiper
Dozer Blade Width: 8' 6"	Air suspension seat
Maximum Dig Depth: 18' 0"	Two speed travel with automatic shift down
Bucket Digging Force: 22,188 lbs.	Travel alarm
Tail Swing Radius: 6' 9"	Arm & Boom holding valve with lift alarm
Horsepower / RPM: 103.3 / 2,000	Control pattern selector valve
EPA Interim Tier 4 Compliant	Pilot operated joystick controls with safety lock out
Travel Speed: 1.9 / 3.3 mph	Wrap around counterweight
Auxiliary Flow: (Primary) 59 gpm	Adjustable air suspension seat with retractable seat belt
Auxiliary Flow: (Secondary) 14.5 gpm	Primary and Secondary two-way auxiliary hydraulic circuits routed to the end of the arm
Boom swing: Left 77° / Right 53°	Electrohydraulic push button controls of auxiliary hydraulic circuit (Primary Only)
24" Wide Steel Tracks	Proportional thumb control of both auxiliary hydraulic circuits
Optional: 20" Rubber Track	Variable displacement axial piston main hydraulic pumps
Optional: 20" Road Liner style tracks	LCD gauge panel with multi-function operator information center
	Heavy duty dozer blade with Float
	Accumulator

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TB1140	TB1140 Equipped with CAB, Rubber or Steel Tracks, Dozer blade with float, Auto Air Conditioner/Heat, Defroster, Windshield wiper and washer, Control pattern selector valve, Travel alarm, Cab light, Auxiliary hydraulics (primary and secondary), Slide back front window, AM/FM/MP3 radio, Air Suspension seat, Engine monitoring system	\$160,395
TB1140CL (w/ Road Liner Tracks)	TB1140 Cab (above Equipped except with Road Liner Tracks)	\$169,343

BASE MACHINE PRICE DOES NOT INCLUDE BUCKET

ATTACHMENTS

BMC1140	Mechanical Coupler, Pin Grabber type with Pins (700 lbs)	\$5,130
BTB114018	18" Pin-On Bucket (Capacity 0.41) (875 lbs)	\$2,745
BTB114024	24" Pin-On Bucket (Capacity 0.57) (1025 lbs)	\$2,825
BTB114030	30" Pin-On Bucket (Capacity 0.73) (1110 lbs)	\$3,385
BTB114036	36" Pin-On Bucket (Capacity 0.89) (1295 lbs)	\$3,660
BTB114042D	42" Pin-On Ditching Bucket (Capacity 0.50) (695 lbs)	\$2,708
BTB114048D	48" Pin-On Ditching Bucket (Capacity 0.60) (800 lbs)	\$2,915
BTB114054D	54" Pin-On Ditching Bucket (Capacity 0.70) (900 lbs)	\$3,130
BTB114060D	60" Pin-On Ditching Bucket (Capacity 0.80) (970 lbs)	\$3,335
BTH1140I	INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs)	\$7,765
BTH1140LI	INSTALLED Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler)	\$7,765

FIELD INSTALLED OPTIONS

K1573400001	3" Retractable seat belt in lieu of standard 2"	\$123
BTH1140K	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets Only) (835 lbs)	\$7,305
BTH1140LK	Hydraulic thumb (Compatible with 24" and larger PIN ON buckets and Mechanical Coupler)	\$7,305
TB1140BKTPINS	Bucket Pin Kit (includes Hardware)	\$482

TAKEUCHI

TL8 Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

<p>Operating Weight: 8,345 lbs. Overall Width Without Bucket: (12"/15" Tracks) 62"/ 65" Tipping Load (SAE 732) 6,020 lbs. Rated Operating Capacity (ROC)(SAE J818): 2,105 lbs Bucket Digging Force: 6,834 lbs. Horsepower / RPM: 74.3 / 2,600 Travel Speed: 4.5 / 6.8 mph Auxiliary Flow: 18.4 gpm Ground Pressure: 4.4 psi Maximum Lift Height to Bucket Pin: 9' 11" Reach Fully Raised: 2' 4.7" Canopy/Cab height: 6' 11.9" / 7' 4"</p> <p>EPA Final Tier 4 Turbocharged Engine with DPF</p>	<p>ROPS/FOPS tilt-up operators compartment w/ RH/LH rearview mirrors Back-up alarm, Top and rear windows Automatic fuel bleed system Pilot operated joystick controls Universal quick attach mounting bracket Six-way adjustable suspension seat with retractable seatbelt One and two way auxiliary hydraulics Electronic engine monitoring system Electrohydraulic push button controls of auxiliary hydraulic circuit Proportional slide switch control auxiliary hydraulics with detent function Hydraulic self-leveling bucket Flat face, pressure releasing Hydraulic Couplers Standard 14-pin connector with push button control Dual element air cleaner with standard pre-cleaner Push button boom float with detent Foot Throttle</p>
--	---

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL8RW	TL8 with ROPS/FOPS Canopy, 15" Rubber tracks	\$53,303
TL8RWP (w/ PC)	TL8RW (above Equipped) with Pattern Control*	\$54,281
TL8CRW	TL8 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15" Rubber Tracks, Hydraulic quick attach, Roll up door	\$59,483
TL8CRWP (w/ PC)	TL8CRW (above Equipped) with Pattern Control*	\$60,461
<hr/>		
TL8RN	TL8 with ROPS/FOPS Canopy, 12" Rubber tracks	\$52,816
TL8RNP (w/ PC)	TL8RN (above Equipped) with Pattern Control*	\$53,795
TL8CRN	TL8 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 12" Rubber Tracks, Hydraulic quick attach, Roll up door	\$58,996
TL8CRNP (w/ PC)	TL8CRN (above Equipped) with Pattern Control*	\$59,975

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET
* PC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS

NOTE: 67" and 76" buckets work with both 12" / 15" Track's

BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	\$1,570
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	\$1,465
ABLU-72S-057	72" Low Profile Bucket - Smooth with Bolt on Cutting Edge	\$1,612
ABLU-72T-057	72" Low Profile Bucket -Tooth	\$1,523
BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,040
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$1,895
BPL1200	7' six way dozer blade	\$6,325
BTLPF48	HD 48" pallet forks and frame	\$1,185
K28854701I	Radio kit installed (AM/FM/MP3)	\$500
K48834204I	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
K48834204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28833001	Counter Weight Kit TL8 (350 lbs)(Increase ROC to 2,323 lb)	\$900
K488710000	H pattern fixed control kit for TL8	\$353
K48837001	TL8 hydraulic quick attach coupler kit (for Canopy unit)	\$1,560
K28854701	Radio kit (AM/FM/MP3)	\$421
1903908050	Active Power Control Kit (Field Kit)	\$300

Prices and specifications
subject to change without notice

P-9-A
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2016

TAKEUCHI

TL8

Track Loader
HIGH FLOW

519 Bonnie Valentine Way Pendergrass, GA 30567
Tel 706-693-3600 Fax 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 8,620 lbs.	ROPS/FOPS tilt-up operators compartment w/ RH/LH rearview mirrors
Overall Width Without Bucket (w/ 15" Tracks): 65"	Back-up alarm, Top and rear windows
Tipping Load (SAE 732): 6,020 lbs.	Automatic fuel bleed system
Rated Operating Capacity (ROC)(SAE J818): 2,105 lbs	Pilot operated joystick controls
Bucket Digging Force: 6,834 lbs.	Universal quick attach mounting bracket
Horsepower / RPM: 74.3 / 2,600	Six-way adjustable suspension seat with retractable seatbelt
Travel Speed: 4.5 / 6.8 mph	One and two way auxiliary hydraulics
Auxiliary Flow: 18.4 gpm STD / 33 gpm HF	Electronic engine monitoring system
Ground Pressure: 4.5 psi	Electrohydraulic push button controls of auxiliary hydraulic circuit
Maximum Lift Height to Bucket Pin: 9' 11"	Proportional slide switch control auxiliary hydraulics with detent function
Reach Fully Raised: 2' 4.7"	Hydraulic self-leveling bucket
Cab height: 7' 4"	1/2" Flat face, pressure relieving Hydraulic Couplers
1/2" Lexan roll up door	Standard 14-pin connector with push button control
EPA Final Tier 4 turbocharged engine with DPF	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent
	Foot throttle

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL8CRWH	TL8 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 15" Rubber Tracks, Hydraulic quick attach, Lexan Roll up door and HIGH FLOW auxiliary hydraulics (33 gpm)	\$62,315
TL8CRWHP (w/ PC)	TL8CRW (above Equipped) with Pattern Control*	\$63,294

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET
* PC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS

BTL867	67" HD smooth dirt bucket with bolt-on edge, 14.0 cubic feet capacity	\$1,570
BTL867T	67" HD dirt bucket with 7 teeth, 14.0 cubic feet capacity	\$1,465
ABLU-72S-057	72" Low Profile Bucket - Smooth with Bolt on Cutting Edge	\$1,612
ABLU-72T-057	72" Low Profile Bucket -Tooth	\$1,523
BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,040
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$1,895
BPL1200	7' six way dozer blade	\$6,325
BTLPF48	HD 48" pallet forks and frame	\$1,185
K28854701I	Radio kit installed (AM/FM/MP3)	\$500
K48834204I	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
K48834204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28833001	Counter Weight Kit TL8 (350 lbs)(Increase ROC to 2,323 lb)	\$900
K488710000	H pattern fixed control kit for TL8	\$353
K28854701	Radio kit (AM/FM/MP3)	\$421
1903908050	Active Power Control Kit (Field Kit)	\$300

Prices and specifications
subject to change without notice

P-9-B
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2016

TAKEUCHI

TL10

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 10,318 lbs.	ROPS/FOPS tilt-up operators compartment with foot throttle
Overall Width Without Bucket: 69.7"	Back-up alarm
Tipping Load (SAE 732) 8,867 lbs.	Top and rear windows
Rated Operating Capacity (ROC)(SAE J818) 2,403 lbs	Automatic fuel bleed system
Bucket Digging Force: 7,400 lbs.	Pilot operated joystick controls
Horsepower / RPM: 90.7 / 2,400	Universal quick attach mounting bracket
Travel Speed: 4.6 / 7.2	Six-way adjustable suspension seat with retractable seatbelt
Auxiliary Flow: 20 gpm	One and two way auxiliary hydraulics
Ground Pressure: 4.4 PSI	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 10' 3"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 34.4"	Proportional slide switch control auxiliary hydraulics with detent function
Canopy/Cab height: 7' 5.4"	Hydraulic self-leveling bucket
Front & rear working lights	Flat face, pressure relieving Hydraulic Couplers
Level 2 FOPS operator protection	Standard 14-pin connector with push button control
Selectable Hydraulic Modes	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL10R	TL10 with ROPS/FOPS Canopy, 17.7" Rubber tracks	\$64,025
TL10RR (w/ RC)	TL10R (above Equipped) with Ride Control*	\$64,725
TL10RP (w/ PC)	TL10R (above Equipped) with Pattern Control*	\$64,975
TL10RRP (w/ RC & PC)	TL10R (above Equipped) with Ride Control & Pattern Control*	\$65,675

TL10CR	TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door	\$70,495
TL10CRR (w/ RC)	TL10CR (above Equipped) with Ride Control*	\$71,195
TL10CRP (w/ PC)	TL10CR (above Equipped) with Pattern Control*	\$71,445
TL10CRRP (w/ RC & PC)	TL10CR (above Equipped) with Ride Control & Pattern Control*	\$72,145

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,040
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$1,895
BPL1200	7' six way dozer blade	\$6,325
BTLPF48	HD 48" pallet forks and frame	\$1,185
K28854701I	Radio kit installed (AM/FM/MP3)	\$500
K28854204I	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

FIELD/INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91
K28854204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28854701	Radio kit (AM/FM/MP3)	\$421
K28839903	H pattern fixed control kit for TL10/TL12	\$375
K38847001	TL10 hydraulic quick attach coupler kit (for Canopy unit)	\$1,630
K28853001	Counterweight kit for TL10 (575 lbs) - Increase in ROC to 2,723 lbs	\$1,550
1903908060	Active Power Control Kit (Field Kit)	\$300
K388440000	TL10 cold weather panel kit	\$120

Prices and specifications
subject to change without notice

P-10-A
Prices are in US Dollar

Prices are F.O.B. Pendergrass,GA
Effective 1 January 2016

TAKEUCHI

TL10

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725

www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 10,516 lbs.	ROPS/FOPS tilt-up operators compartment with foot throttle
Overall Width Without Bucket: 69.7"	Back-up alarm
Tipping Load (SAE 732): 8,867 lbs.	Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,403 lbs	Automatic fuel bleed system
Bucket Digging Force: 7,400 lbs.	Pilot operated joystick controls
Horsepower / RPM: 90.7 / 2,400	Universal quick attach mounting bracket
Travel Speed: 4.6 / 7.2	Six-way adjustable suspension seat with retractable seatbelt
Auxiliary Flow (SP1): 20 gpm STD / 36 gpm HF	One and two way auxiliary hydraulics
Auxiliary Flow (SP2): 17 gpm	Electronic engine monitoring system
Ground Pressure: 4.4 PSI	Electrohydraulic push button controls of auxiliary hydraulic circuit
Maximum Lift Height to Bucket Pin: 10' 3"	Proportional slide switch control auxiliary hydraulics with detent function
Reach Fully Raised: 34.4"	Hydraulic self-leveling bucket
Canopy/Cab height: 7' 5.4"	Flat face, pressure relieving Hydraulic Couplers
Front & rear working lights	Standard 14-pin connector with push button control
Level 2 FOPS operator protection	Dual element air cleaner with standard pre-cleaner
Selectable Hydraulic Modes	Push button boom float with detent

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL10CRH	TL10 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line	\$73,545
TL10CRHR (w/ RC)	TL10CRH (above Equipped) with Ride Control*	\$74,245
TL10CRHP (w/ PC)	TL10CRH (above Equipped) with Pattern Control*	\$74,495
TL10CRHRP (w/ RC & PC)	TL10CRH (above Equipped) with Ride Control & Pattern Control*	\$75,195

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1076	76" HD smooth dirt bucket with bolt-on edge, 20.3 cubic feet capacity	\$2,040
BTL1076T	76" HD dirt bucket with 8 teeth, 20.3 cubic feet capacity	\$1,895
BPL1200	7' six way dozer blade	\$6,325
BTLPF48	HD 48" pallet forks and frame	\$1,185
K288547011	Radio kit installed (AM/FM/MP3)	\$500
K288542041	3-point 2" seat belt kit installed (in lieu of standard 2")	\$190

FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91
K28854204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28854701	Radio kit (AM/FM/MP3)	\$421
K28839903	H pattern fixed control kit for TL10/TL12	\$375
K28853001	Counterweight kit for TL10 (575 lbs) - Increase in ROC to 2,723 lbs	\$1,550
1903908060	Active Power Control Kit (Field Kit)	\$300
K388440000	TL10 cold weather panel kit	\$120

Prices and specifications
subject to change without notice

P-10-B
Prices are in US Dollar

Prices are F.O.B. Pendergrass,GA
Effective 1 January 2016

TAKEUCHI

TL12

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel 706-693-3800 Fax: 706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 11,618 lbs.	ROPS/FOPS tilt-up operators compartment with foot throttle
Overall Width Without Bucket: 73.2"	Back-up alarm
Tipping Load (SAE 732) 8,102 lbs.	Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,833 lbs	Automatic fuel bleed system
Bucket Digging Force: 8,670 lbs.	Pilot operated joystick controls
Horsepower / RPM: 108.4 / 2,400	Universal quick attach mounting bracket
Travel Speed: 4.9 / 7.4 mph	Six-way adjustable suspension seat with retractable seatbel
Auxiliary Flow: 23 gpm	One and two way auxiliary hydraulics
Ground Pressure: 4.6 psi	Electronic engine monitoring system
Maximum Lift Height to Bucket Pin: 10' 6"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Reach Fully Raised: 38.8"	Proportional slide switch control auxiliary hydraulics with detent function
Canopy/Cab height: 7' 7.3"	Hydraulic self-leveling bucket
Front & rear working lights	Flat face, pressure relieving Hydraulic Couplers
Level 2 FOPS operator protection	Standard 14-pin connector with push button control
Selectable Hydraulic Modes	Dual element air cleaner with standard pre-cleaner
	Push button boom float with detent

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12R	TL12 with ROPS/FOPS Canopy, 17.7" Rubber tracks	\$76,845
TL12RR (w/ RC)	TL12R (above Equipped) with Ride Control*	\$77,545
TL12RP (w/ PC)	TL12R (above Equipped) with Pattern Control*	\$77,795
TL12RRP (w/ RC & PC)	TL12R (above Equipped) with Ride Control & Pattern Control*	\$78,495

TL12CR	TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door	\$83,395
TL12CRR (w/ RC)	TL12CR (above Equipped) with Ride Control*	\$84,095
TL12CRP (w/ PC)	TL12CR (above Equipped) with Pattern Control*	\$84,345
TL12CRRP (w/ RC & PC)	TL12CR (above Equipped) with Ride Control & Pattern Control*	\$85,045

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET
 * PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$2,270
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$2,095
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu ft. capacity	\$2,570
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	\$2,472
BPL12008	8' six way dozer blade	\$6,500
BTLPF48	HD 48" pallet forks and frame	\$1,185
K288547011	Radio kit Installed (AM/FM/MP3)	\$500
K288542041	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

FIELD INSTALLED OPTIONS

19141-99948	3" retractable seat belt in lieu of standard 2"	\$91
K28854204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28854701	Radio kit (AM/FM/MP3)	\$421
K28839903	H pattern fixed control kit for TL10/TL12	\$375
K38857001	TL12 hydraulic quick attach coupler kit (for Canopy unit)	\$1,630
K28853001	Counterweight kit for TL12 (575 lbs) - Increase in ROC to 3,263 lbs	\$1,550
1903908060	Active Power Control Kit (Field Kit)	\$300
K388540000	TL12 cold weather panel kit	\$120

Prices and specifications
 subject to change without notice

P-11-A
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2016

TAKEUCHI

TL12

Track Loader

HIGH FLOW

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel 706-693-3600 Fax 706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 11,850 lbs.	ROPS/FOPS tilt-up operators compartment with foot throttle
Overall Width Without Bucket: 73.2"	Back-up alarm
Tipping Load (SAE 732) 8,102 lbs.	Top and rear windows
Rated Operating Capacity (ROC)(SAE J818): 2,833 lbs	Automatic fuel bleed system
Bucket Digging Force: 8,670 lbs.	Pilot operated joystick controls
Horsepower / RPM: 108.4 / 2,400	Universal quick attach mounting bracket
Travel Speed: 4.9 / 7.4 mph	Six-way adjustable suspension seat with retractable seatbelt
Auxiliary Flow (SP1): 23 gpm STD / 40 gpm HF	One and two way auxiliary hydraulics
Auxiliary Flow (SP2): 17 gpm	Electronic engine monitoring system
Ground Pressure: 4.6 psi	Electrohydraulic push button controls of auxiliary hydraulic circuit
Maximum Lift Height to Bucket Pin: 10' 6"	Proportional slide switch control auxiliary hydraulics with detent function
Reach Fully Raised: 38.8"	Hydraulic self-leveling bucket
Cab height: 7' 7.3"	Flat face, pressure relieving Hydraulic Couplers
Front & rear working lights	Standard 14-pin connector with push button control
Level 2 FOPS operator protection	Dual element air cleaner with standard pre-cleaner
Selectable Hydraulic Modes	Push button boom float with detent

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12CRH	TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line	\$86,395
TL12CRHR (w/ RC)	TL12CRH (above Equipped) with Ride Control*	\$87,095
TL12CRHP (w/ PC)	TL12CRH (above Equipped) with Pattern Control*	\$87,345
TL12CRHRP (w/ RC & PC)	TL12CRH (above Equipped) with Ride Control & Pattern Control*	\$88,045

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$2,270
BTL1280T	80" HD dirt bucket with 8 teeth 24.0 cu ft. capacity	\$2,095
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu.ft. capacity	\$2,570
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth	\$2,472
BPL12008	8' six way dozer blade	\$6,500
BTLPF48	HD 48" pallet forks and frame	\$1,185
K28854701I	Radio kit Installed (AM/FM/MP3)	\$500
K28854204I	3-point 2" seat belt kit Installed (in lieu of standard 2")	\$190

FIELD INSTALLED OPTIONS

1914199948	3" retractable seat belt in lieu of standard 2"	\$91
K28854204	3-point 2" seat belt kit in lieu of standard 2"	\$150
K28854701	Radio kit (AM/FM/MP3)	\$421
K28839903	H pattern fixed control kit for TL10/TL12	\$375
K28853001	Counterweight kit for TL12 (575 lbs) - Increase in ROC to 3,263 lbs	\$1,550
1903908060	Active Power Control Kit (Field Kit)	\$300
K388540000	TL12 cold weather panel kit	\$120

Prices and specifications
 subject to change without notice

P-11-B
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2016

TAKEUCHI

TL12V2

Track Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 12,434 lbs	Vertical boom design
Overall Width Without Bucket: 77.2"	ROPS/FOPS tilt-up operators compartment
Tipping Load (SAE 732) 11,737 lbs.	Electric dial and foot throttle
Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs	Back-up alarm
Bucket Digging Force: 7,884 lbs	Top and rear window
EPA Final Tie 4 with DOC + DPF + SCR	Automatic fuel bleed system
Horsepower / RPM: 111.3 / 2,400	Pilot operated joystick controls
Travel Speed: 5.0 / 7.3 mph	Universal quick attach mounting bracket
Auxiliary Flow: 23.2 gpm	Deluxe high back suspension seat with retractable seatbelt
Ground Pressure: 4.7 psi	One and two way auxiliary hydraulics
Maximum Lift Height to Bucket Pin: 10' 10"	Electronic engine monitoring system
Reach Fully Raised: 36.4"	Electrohydraulic push button controls of auxiliary hydraulic circuit
Canopy/Cab height: 7' 7.6"	Proportional slide switch control auxiliary hydraulics with detent function
Front & rear LED working lights	Hydraulic self-leveling bucket
Selectable working modes	Flat face, pressure relieving hydraulic couplers
Active power control power management system	Standard 14-pin connector with push button control
	Dual element air cleaner
	Push button boom float with detent

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12V2-R	TL12V with ROPS/FOPS Canopy, 17.7" Rubber tracks	\$83,500
TL12V2-RR (w/ RC)	TL12VR (above Equipped) with Ride Control*	\$84,200
TL12V2-RP (w/ PC)	TL12VR (above Equipped) with Pattern Control*	\$84,450
TL12V2-RRP (w/ RC & PC)	TL12VR (above Equipped) with Ride Control & Pattern Control*	\$85,150

TL12V2-CR	TL12V with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, AM/FM Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up door	\$90,050
TL12V2-CRR (w/ RC)	TL12VCR (above Equipped) with Ride Control*	\$91,200
TL12V2-CRP (w/ PC)	TL12VCR (above Equipped) with Pattern Control*	\$91,450
TL12V2-CRRP (w/ RC & PC)	TL12VCR (above Equipped) with Ride Control & Pattern Control*	\$92,150

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET

* PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$2,270
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$2,095
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu ft. capacity	\$2,570
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity	\$2,472
BPL12008	8' six way dozer blade	\$8,500
BTLPF48	HD 48" pallet forks and frame	\$1,185

FIELD INSTALLED OPTIONS

Prices and specifications
 subject to change without notice

P-11-C
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2016

TAKEUCHI

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-us.com

TL12V2

Track Loader
 HIGH FLOW

STANDARD EQUIPMENT

Operating Weight: 12,756 lbs
 Overall Width Without Bucket: 77.2"
 Tipping Load (SAE 732) 11,737 lbs.
 Rated Operating Capacity (ROC)(SAE J818): 4,107 lbs
 Bucket Digging Force: 7,884 lbs.
 EPA Final Tie 4 with DOC + DPF + SCR
 Horsepower / RPM: 111.3 / 2,400
 Travel Speed: 5.0 / 7.3 mph
 Auxiliary Flow (Std / High Flow) 23.2 gpm / 40 gpm
 Ground Pressure: 4.7 psi
 Maximum Lift Height to Bucket Pin: 10' 10"
 Reach Fully Raised: 36.4"
 Canopy/Cab height: 7' 7.6"

Vertical boom design
 ROPS/FOPS tilt-up operators compartment
 Electric dial and foot throttle
 Back-up alarm
 Top and rear window
 Automatic fuel bleed system
 Pilot operated joystick controls
 Universal quick attach mounting bracket
 Deluxe high back suspension seat with retractable seatbelt
 One and two way auxiliary hydraulics
 Electronic engine monitoring system
 Electrohydraulic push button controls of auxiliary hydraulic circuit
 Proportional slide switch control auxiliary hydraulics with detent function
 Hydraulic self-leveling bucket
 Flat face, pressure relieving hydraulic couplers
 Standard 14-pin connector with push button control
 Dual element air cleaner
 Push button boom float with detent

Front & rear LED working lights
 Selectable working modes
 Active power control power management system

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TL12V2-CRH	TL12 with ROPS/FOPS Cab with Air Conditioning/Heat, Defroster, AM/FM Radio, 17.7" Rubber Tracks, Hydraulic quick attach, Roll up Lexan door HIGH FLOW Auxiliary Hydraulics w/ second auxiliary line	\$93,050
TL12V2-CRHR (w/ RC)	TL12VCRH (above Equipped) with Ride Control*	\$93,750
TL12V2-CRHP (w/ PC)	TL12VCRH (above Equipped) with Pattern Control*	\$94,000
TL12V2-CRHRP (w/ RC & PC)	TL12VCRH (above Equipped) with Ride Control & Pattern Control*	\$94,700

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET
 * PC & RC requires a minimum of 90 days delivery time for factory order

ATTACHMENTS / OPTIONS

BTL1280	80" HD smooth dirt bucket with bolt-on edge, 24.0 cu ft. capacity	\$2,270
BTL1280T	80" HD dirt bucket with 9 teeth 24.0 cu.ft. capacity	\$2,095
ABLU-84S-100	84" High Capacity - HD Dirt Bucket - Smooth with bolt-on edge, 27 cu ft. capacity	\$2,570
ABLU-84T-100	84" High Capacity - HD Dirt Bucket - Tooth - 27 cu.ft. capacity	\$2,472
BPL12008	8' six way dozer blade	\$6,500
BTLPF48	HD 48" pallet forks and frame	\$1,185

FIELD INSTALLED OPTIONS

Prices and specifications
 subject to change without notice

P-11-D
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2016

TAKEUCHI

TW40 Wheel Loader

519 Bonnie Valentine Way, Pendergrass, GA 30567
Tel:706-693-3600 Fax:706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

Operating Weight: 7,275 lbs	Back-Up Alarm
Tip Load, Straight: 5,842 lbs	Front Working Lights
Bucket breakout force: 7,126 lbs	Rear Working Lights
HP / RPM: 39.4 hp / 2,800 rpm	Inching Pedal
Travel Speed (Max): 12.4 gpm	Front Limited Slip Axle 45%
Auxiliary Flow: 10.3 gpm	Auxiliary Hydraulic Lines
Maximum Height to Bucket pin: 9' 7.7"	Replaceable Bushings
Height: (Canopy) 8' / (Cab) 8' 2"	Bucket Float
Articulation: 40 /40	Automatic Bucket Positioning
Lift Capacity @ G. L.: 5,260 lb	Heavy Duty Hydraulic SSL Style Quick Attach Coupler
Reach fully raised: 2' 8.5"	Center Pivot Steering
	Heavy Duty 31x15.5-15 Construction Tire Assembly
	Optional heated Cab features front/rear wiper and rear defrost

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW40	TW40 with Foldable ROPS Canopy and Tires	\$55,105
TW40C	TW40 with Cab with Heat and Tires	\$59,740

BASE MACHINE PRICE DOES NOT INCLUDE ATTACHMENTS

ATTACHMENTS

BTW4060	60" General Purpose Bucket (0.66 cu. Yd) for TW40 with SSL Mount	\$2,300
BTW4060A	60" Bolt on Blade for BTW4060	\$282
BTW4060B	60" Tooth Bar for BTW4060 (note: not compatible with bolt on blade)	\$643

FIELD INSTALLED OPTIONS

TWFASTERKIT	TW Series Coupler Kit	\$132
-------------	-----------------------	-------

24% + 10% Net = Net

TAKEUCHI

TW65

Wheel Loader

SERIES 2

519 Bonnie Valentine Way Pendergrass, GA 30567
Tel: 706-693-3600 Fax: 706-693-3725
www.takeuchi-us.com

STANDARD EQUIPMENT

<p>Operating Weight: 11,354 lbs Tip Load, Straight: 9,171 lbs Bucket Breakout Force 11,600 lbs HP / RPM: 73 / 2200 Travel Speed (Max) 12.4 mph Auxiliary Flow: 16.4 gpm Maximum Height to Bucket Pin. 10 ft 4 6 in Height: 8 ft 9,8 in Articulation: 40 / 40 Lift Capacity @ G. L.: 10,319 lbs Reach Fully Raised: 24"</p>	<p>Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities Deluxe suspension seat Pilot operator loader joystick control EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system Side by side radiator and hydraulic oil cooler Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick 100% Front and rear differential lock Euro style attachment mount with hydraulic coupler Bucket float Mechanical bucket positioning Safety features include: ROPS/FOPS enclosed cab, back up alarm, lights retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights, front driving lights, front and rear hazard and directional indicators)</p>
--	---

ORDER PROCEDURE

ORDER STEPS 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW65C2	TW65 Cab	\$83,420
TW65C2HS	TW65 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control	\$87,746
TW65C2HF	TW65 Cab, High Flow Auxiliary Hydraulics (26 gpm)	\$88,271
TW65C2HH	TW65 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control	\$92,597

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW65TIREHD	Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,395
BTW65TIREF	Floatation Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,950

ATTACHMENTS

BTW5077	77" Construction Combo Bucket (1.05 cu. Yd) for TW65/TW80	\$2,520
BTW5077A	77" Bolt on Blade for BTW5077	\$370
BTW8082	81.5" General Purpose Bucket (1.3 cu. Yd) for TW80	\$2,520
BTW8082A	82" Bolt-on Blade for BTW8082	\$370
BTWPF48	48" Combo Fork Assy for all TW's (Rated 8000 lb)	\$2,300
BTWUNIADP	Combo Hitch to Universal SSL Adapter TW50/60/65/80	\$2,200

FIELD INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
TWFASTERKIT	TW Series Coupler Kit	\$132

Prices and specifications
subject to change without notice

P-13
Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
Effective 1 January 2016

TAKEUCHI

TW80

Wheel Loader

SERIES 2

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel: 706-693-3600 Fax: 706-693-3725
 www.takeuchi-us.com

STANDARD EQUIPMENT

<p>Operating Weight: 12,700 lbs Tip Load, Straight: 10,065 lbs Bucket Breakout Force: 12,287 lbs HP / RPM: 73 / 2200 Travel Speed (Max): 12.4 mph Auxiliary Flow: 16.4 gpm Maximum Height to Bucket Pin: 11 ft 1 in Height: 8 ft 11.5 in Articulation: 40 / 40 Lift Capacity @ G. L.: 12,287 lbs Reach Fully Raised: 29"</p>	<p>Enclosed cab w/ air conditioner, heat, front and rear windshield wiper, front and rear washer, rear window defrost LCD Gauge panel with multi-function operator information center with diagnostics and anti-theft capabilities Deluxe suspension seat Pilot operator loader joystick control EPA Final Tier 4 turbocharged engine with DOC and engine monitoring system Side by side radiator and hydraulic oil cooler Proportional thumb wheel control for auxiliary hydraulic circuit located in joystick 100% Front and rear differential lock Euro style attachment mount with hydraulic coupler Bucket float Mechanical bucket positioning Safety features include: ROPS/FOPS enclosed cab, back up alarm, lights retractable seatbelt, control lockout, and deluxe lighting package (front and rear working lights, front driving lights, front and rear hazard and directional indicators)</p>
--	--

ORDER PROCEDURE

ORDER STEPS: 1. Choose base model 2. Choose Tire Option 3. Choose Attachments

BASE MACHINE WITH STANDARD EQUIPMENT

Factory Code	Description	Suggested List Price
TW80C2	TW80 Cab	\$92,690
TW80C2HS	TW80 Cab, High Speed Road Gear (24.8 mph max speed), & Ride Control	\$97,016
TW80C2HF	TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm)	\$97,541
TW80C2HH	TW80 Cab, High Flow Auxiliary Hydraulics (26 gpm), High Speed Road Gear (24.8 mph max speed), & Ride Control	\$101,867

BASE MACHINE PRICE DOES NOT INCLUDE A BUCKET or TIRES

TIRE OPTION (BASE MACHINE DOES NOT INCLUDE TIRES)

BTW65TIREHD	Heavy Duty Construction Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,395
BTW65TIREF	Floatation Tire Assy for TW65 / TW80 (4 x Tire Assy)	\$3,950

ATTACHMENTS

BTW8082	81.5" General Purpose Bucket (1.3 cu. Yd) for TW80	\$2,520
BTW8082A	82" Bolt-on Blade for BTW8082	\$370
BTWPF48	48" Combo Fork Assy for all TW's (Rated 8000 lb)	\$2,300
BTWUNIADP	Combo Hitch to Universal SSL Adapter TW50/60/65/80	\$2,200

FIELD/INSTALLED OPTIONS

1914199948	3" Retractable seat belt in lieu of standard 2"	\$91
TWFASTERKIT	TW Series Coupler Kit	\$132

Prices and specifications
 subject to change without notice

P-14
 Prices are in US Dollar

Prices are F.O.B. Pendergrass, GA
 Effective 1 January 2016



P3-Power Protection Plan

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

Excavators

		Model	TB 108	TB 216	TB230	TB240
2YR/2000HR	Full Machine	Item #	n/a	n/a	n/a	n/a
2YR/2000HR	Full Machine	List	std	std	std	std
3YR/3000HR	Power train	Item_Number	EW108P32	EW216P31	EW230P31	EW240P31
3YR/3000HR	Power train	List	\$478	\$628	\$844	\$1,157
3YR/3000HR	Power Train & Hydraulic	Item_Number	EW108PH32	EW216PH31	EW230PH31	EW240PH31
3YR/3000HR	Power Train & Hydraulic	List	\$797	\$1,047	\$1,407	\$1,928
3YR/3000HR	Full Machine	Item_Number	EW108FM32	EW216FM31	EW230FM31	EW240FM31
3YR/3000HR	Full Machine	List	\$996	\$1,308	\$1,759	\$2,410
4YR/4000HR	Power train	Item_Number	EW108P42	EW216P41	EW230P41	EW240P41
4YR/4000HR	Power train	List	\$1,116	\$1,465	\$1,970	\$2,699
4YR/4000HR	Power Train & Hydraulic	Item_Number	EW108PH42	EW216PH41	EW230PH41	EW240PH41
4YR/4000HR	Power Train & Hydraulic	List	\$1,714	\$2,250	\$3,025	\$4,145
5YR/5000HR	Power train	Item_Number	EW108P52	EW216P51	EW230P51	EW240P51
5YR/5000HR	Power train	List	\$1,275	\$1,675	\$2,251	\$3,085
5YR/5000HR	Power Train & Hydraulic	Item_Number	EW108PH52	EW216PH51	EW230PH51	EW240PH51
5YR/5000HR	Power Train & Hydraulic	List	\$1,953	\$2,564	\$3,447	\$4,723

			TB260	TB290	TB290FR	TB 1140
2YR/2000HR	Full Machine	Item #	n/a	n/a	n/a	n/a
2YR/2000HR	Full Machine	List	std	std	std	std
3YR/3000HR	Power train	Item #	EW260P31	EW290P31	EW280P31	EW1140P32
3YR/3000HR	Power train	List	\$1,572	\$2,147	\$2,276	\$3,045
3YR/3000HR	Power Train & Hyd	Item #	EW260PH31	EW290PH31	EW280PH31	EW1140PH32
3YR/3000HR	Power Train & Hyd	List	\$2,621	\$3,578	\$3,794	\$5,075
3YR/3000HR	Full Machine	Item #	EW260FM31	EW290FM31	EW280FM31	EW1140FM32
3YR/3000HR	Full Machine	List	\$3,276	\$4,472	\$4,742	\$6,344
4YR/4000HR	Power train	Item #	EW260P41	EW290P41	EW280P41	EW1140P42
4YR/4000HR	Power train	List	\$3,669	\$5,009	\$5,311	\$7,105
4YR/4000HR	Power Train & Hyd	Item #	EW260PH41	EW290PH41	EW280PH41	EW1140PH42
4YR/4000HR	Power Train & Hyd	List	\$5,635	\$7,692	\$8,157	\$10,912
5YR/5000HR	Power train	Item #	EW260P51	EW290P51	EW280P51	EW1140P52
5YR/5000HR	Power train	List	\$4,193	\$5,724	\$6,070	\$8,120
5YR/5000HR	Power Train & Hyd	Item #	EW260PH51	EW290PH51	EW280PH51	EW1140PH52
5YR/5000HR	Power Train & Hyd	List	\$6,421	\$8,765	\$9,295	\$12,434

For pricing on older models, please visit www.takeuchi-us.com under the P3 section



P3-Power Protection Plan

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

Track Loaders

			TL8	TL10	TL10H	TL12	TL12H
2YR/2000HR	Full Machine	Item Number	n/a	n/a	n/a	n/a	n/a
2YR/2000HR	Full Machine	List	std	std	std	std	std
3YR/3000HR	Power train	Item Number	EWL8P31	EWL10P31	EWL10HP31	EWL12P31	EWL12HP31
3YR/3000HR	Power train	List	\$1,033	\$1,343	\$1,473	\$1,600	\$1,747
3YR/3000HR	Power Train & Hydraulic	Item Number	EWL8PH31	EWL10PH31	EWL10HHP31	EWL12PH31	EWL12HHP31
3YR/3000HR	Power Train & Hydraulic	List	\$1,722	\$2,238	\$2,454	\$2,667	\$2,912
3YR/3000HR	Full Machine	Item Number	EWL8FM31	EWL10FM31	EWL10HFM31	EWL12FM31	EWL12HFM31
3YR/3000HR	Full Machine	List	\$2,153	\$2,798	\$3,068	\$3,333	\$3,640
4YR/4000HR	Power train	Item Number	EWL8P41	EWL10P41	EWL10HP41	EWL12P41	EWL12HP41
4YR/4000HR	Power train	List	\$2,411	\$3,133	\$3,436	\$3,733	\$4,077
4YR/4000HR	Power Train & Hydraulic	Item Number	EWL8PH41	EWL10PH41	EWL10HHP41	EWL12PH41	EWL12HHP41
4YR/4000HR	Power Train & Hydraulic	List	\$3,703	\$4,812	\$5,277	\$5,733	\$6,261
5YR/5000HR	Power train	Item Number	EWL8P51	EWL10P51	EWL10HP51	EWL12P51	EWL12HP51
5YR/5000HR	Power train	List	\$2,756	\$3,581	\$3,927	\$4,266	\$4,659
5YR/5000HR	Power Train & Hydraulic	Item Number	EWL8PH51	EWL10PH51	EWL10HHP51	EWL12PH51	EWL12HHP51
5YR/5000HR	Power Train & Hydraulic	List	\$4,219	\$5,483	\$6,013	\$6,533	\$7,134

For pricing on older models, please visit www.takeuchi-us.com under the P3 section



P3-Power Protection Plan

519 Bonnie Valentine Way, Pendergrass, GA 30567
 Tel:706-693-3600 Fax:706-693-3725
 www.takeuchi-us.com

Please visit the dealer portal for more detail on the Power Protection Plan or call the Pendergrass office.

Wheel Loaders

			TW 40	TW 65	TW80
2YR/2000HR	Full Machine	Item_Number	n/a	n/a	n/a
2YR/2000HR	Full Machine	List	std	std	std
3YR/3000HR	Power train	Item_Number	EW40P32	EW65P32	EW80P32
3YR/3000HR	Power train	List	\$1,068	\$1,483	\$1,687
3YR/3000HR	Power Train & Hydraulic	Item_Number	EW40PH32	EW65PH32	EW80PH32
3YR/3000HR	Power Train & Hydraulic	List	\$1,780	\$2,471	\$2,829
3YR/3000HR	Full Machine	Item_Number	EW40FM32	EW65FM32	EW80FM32
3YR/3000HR	Full Machine	List	\$2,226	\$3,089	\$3,536
4YR/4000HR	Power train	Item_Number	EW40P42	EW65P42	EW80P42
4YR/4000HR	Power train	List	\$2,493	\$3,459	\$3,960
4YR/4000HR	Power Train & Hydraulic	Item_Number	EW40PH42	EW65PH42	EW80PH42
4YR/4000HR	Power Train & Hydraulic	List	\$3,828	\$5,313	\$6,082
5YR/5000HR	Power train	Item_Number	EW40P52	EW65P52	EW80P52
5YR/5000HR	Power train	List	\$2,849	\$3,954	\$4,526
5YR/5000HR	Power Train & Hydraulic	Item_Number	EW40PH52	EW65PH52	EW80PH52
5YR/5000HR	Power Train & Hydraulic	List	\$4,362	\$6,054	\$6,931

For pricing on older models, please visit www.takeuchi-us.com under the P3 sector