

**TRUCK, 4 X 4, SIX (6) FOOT STRAIGHT SIDE BED, AUTO TRANSMISSION
2010 SPECIFICATIONS**

Previous Std. Specs.	CHEVROLET / GMC	DODGE	FORD		
	CK10703 TK10703	DS6L61	F150 F1E		
1. All Std Equipment as Listed by Mfg. or as Req. for GVWR 6350 WB 119" to 126" Aprox. 6' Bed	6400 GVW 1858 PL 6 ½ Ft 119 WB	6350 GVW 1880 PL 6.3 Ft 120 WB	6650 GVW 1680 PL 6 ½ Ft 126 WB		
2.a. Engine 4.6L V8 EFI	4.8 L V8 302 5600 305 4600	N/A	4.6L V8 248 4750 294 4000		
2.b. Engine, Flex Fuel (E-85) 4.7L V8	5.3L V-8 315 5200 335 4000	4.7L V-8 310 5600 330 3950	5.4L 3 Valve V8 320 5200 390 3500		
2.c. Engine, Hybrid	N/A	N/A	N/A		
3. Transmission 4 Speed w/Ext./Int. Aux Oil Cooler	4 Speed Auto OD	4 Spd Auto OD	Elec 4 Speed AOD Cooler Std		
3a. Optional Transmission	6 Spd Auto w/Overdrive Flex Fuel Engine only	None	6 Spd Auto w/Overdrive Flex Fuel Engine only		

**TRUCK, 4 X 4, SIX (6) FOOT STRAIGHT SIDE BED, AUTO TRANSMISSION
2010 SPECIFICATIONS**

Previous Std. Specs.	CHEVROLET / GMC	DODGE	FORD		
4. Tires, 5, All Terrain Radial BW to be Mfg. Std to meet GVWR With Manufacturer Standards Spare	P265/70R17 ALL SEASON	P265/70R17 All Season	P235/75R17 BSW All Terrain		
4a. Optional Tires	ON OF ROAD P265 70 R17	None	P265/70R/17 All Terrain		
5. Brakes, 4 wheel ABS Required	4 Wheel ABS	Std	Std Disc 4 Wheel ABS		
6. Battery, 12V Min 600 CCA Mtc Free	600	625	750		
6a Optional Battery	730	None	None		
7. Alternator Min 135 Amp	145	136	135		
8. Power Steering	Std	Std	Std		
9. Mirrors, Ext. Rt./Lft Side Swing Away Factory Installed, Power	Opt	Opt	Std		
10. Bumper, Rear Step Type Painted Mfg. Dealer Installed 400/4000	Std	Std	Std		

**TRUCK, 4 X 4, SIX (6) FOOT STRAIGHT SIDE BED, AUTO TRANSMISSION
2010 SPECIFICATIONS**

Previous Std. Specs.	CHEVROLET / GMC	DODGE	FORD		
11. Radio AM/FM Factory Installed	AM/FM Stereo	AM/FM Stereo W/ Cassette	AM/FM		
12. Dome Light	Std	Std	Std		
13. Carrier, Spare Wheel Underframe	Std	Std	Std		
14. Air Conditioner Factory Installed	Std	Std	Opt		
15. Tinted Glass All Windows	Std	Std	Std		
16. Power Outlet, 12V	2 outlets	1 Outlet	1 Outlet		
17. Air Bag D/S	Dual – Std	Dual – Std	Dual – Std		
18. Fuel Tank - Min 26 Gallons	26	26	26		

**TRUCK, 4 X 4, SIX (6) FOOT STRAIGHT SIDE BED, AUTO TRANSMISSION
2010 SPECIFICATIONS**

Previous Std. Specs.	CHEVROLET / GMC	DODGE	FORD		
19. Differential Limited Slip	Opt	Electronic Stability Program	Opt		
20. Transfer Case 2 Speed	Std	N/A	Std		
21. Skid Plates - For Transfer Case	Opt (Fuel Tank has plastic guard on tank)	Opt - Dealer - Fuel Tank	Opt Fuel & Transfer Case		
22. Hubs - Front Wheel Auto Locking	Std	Std	Std		
23. Vehicle to be Comp Winterized	Std	Std	Std		
24. Fuel 1/4 Tank Upon Delivery	Dealer	Dealer	Dealer		

**TRUCK, 4 X 4, SIX (6) FOOT STRAIGHT SIDE BED, AUTO TRANSMISSION
2010 SPECIFICATIONS**

Previous Std. Specs.	CHEVROLET / GMC	DODGE	FORD		
25. Standard Warranty 36/36	3 Yr. 36,000 Mi 5 Yr 100,000 Mi Drive Train	3 Yr. 36,000 Mi	3 Yr. 36,000 Mi 5 Yr. 60,000 Mi Powertrain		

Optional Equipment					
A. Winch - Min 9000 lb Attached to factory Installed Front Buper & reinforced to frame rails	Dealer	Dealer	Dealer		
B. Anti Lock Brakes	4 Wheel ABS	Std	Std 4 Wheel ABS		
C. Factory Paint Dark Green	Yes - all plastic parts are black	50 or More	5 or More VSO		

**TRUCK, 4 X 4, SIX (6) FOOT STRAIGHT SIDE BED, AUTO TRANSMISSION
2010 SPECIFICATIONS**

Previous Std. Specs.	CHEVROLET / GMC	DODGE	FORD		
D. Optional Engine Size	4.3L V6 SFI 195 4600 260 2800 5.3L V8 315 5200 335 4000 4.8L V8 302 5600 305 4600	5.7L V8 Hemi-Mag 380 5600 404 4000	4.6L 3 Valve 310 5000 365 3500		
E. Grill Guard Wrap around Type Full Cov. May be dealer install	Dealer	Dealer	Dealer		
F. Tow Hooks One Pair	Dealer or MFG	Opt	Opt		
G. Shocks - Heavy Duty Front & Rear	Opt	Std	Std		

**TRUCK, 4 X 4, SIX (6) FOOT STRAIGHT SIDE BED, AUTO TRANSMISSION
2010 SPECIFICATIONS**

Previous Std. Specs.	CHEVROLET / GMC	DODGE	FORD		
<p>H. Auxiliary Battery Minimum 600CCA To include an “isolator” which permits the aux. Battery to be depleted w/out reducing main battery charge which is needed to start vehicle. Alternator to charge both batteries. To be located under hood on the engine compartment and easily accessible to the operator.</p>	N/A	N/A	N/A	N/A	