

**TRUCK, 2 WHEEL DRIVE, EIGHT (8) FOOT BED  
2010 SPECIFICATIONS**

<b>Previous Std. Specs.</b>	<b>CHEVROLET / GMC</b>	<b>DODGE</b>	<b>FORD</b>		
	<b>Silverado CC20903 Sierra TC20903</b>	<b>Ram DH2L62</b>	<b>F2A</b>		
<b>1. All Std Equipment as Listed by Mfg. or as Req. for 8600 GVWR Payload</b>	9200 GVWR 3923 Payload 133" WB	8650 GVW 3820 Payload 8650 - Diesel 5190 Payload 135" WB	8800 GVW 3080 Payload 137" WB		
<b>2.a. Engine, 5.4L V8 EFI</b>	6.0L SFI V8 360 5400 380 4200 Active Fuel Management	5.7L Hemi-Mag 380 5600 404 4000	5.4L V8 300 5000 365 3750		
<b>2.b. Engine, Flex Fuel (E-85)</b>	N/A	N/A	N/A		
<b>2.c. Engine, Hybrid</b>	N/A	N/A	N/A		

**TRUCK, 2 WHEEL DRIVE, EIGHT (8) FOOT BED  
2010 SPECIFICATIONS**

<b>Previous Std. Specs.</b>	<b>CHEVROLET / GMC</b>	<b>DODGE</b>	<b>FORD</b>		
<b>3. Transmission 4 Speed Automatic Overdrive</b>	6 Spd Auto OD	4 Spd Auto OD	5 Spd Auto		
<b>3a. Optional Transmission</b>	None	5 Spd Manual OD w/ Diesel	6 Spd Manual		
<b>4. Tires, 5, All Terrain Radial BW to be Mfg. Std to Meet GVWR</b>	LT245/75R16E All Season or On/Off Road/Spare All Season	LT245/70R17E All Season	LT245/75RX17E BSW All Season		
<b>5. Brakes, Power 4 wheel ABS Required</b>	Std	Std	4Wheel ABS Std		
<b>6. Battery, 12V Min 600 CCA Mntc Free</b>	600	700	650		

**TRUCK, 2 WHEEL DRIVE, EIGHT (8) FOOT BED**  
**2010 SPECIFICATIONS**

<b>Previous Std. Specs.</b>	<b>CHEVROLET / GMC</b>	<b>DODGE</b>	<b>FORD</b>		
<b>6a. Optional Battery</b>	730 Auxiliary Bat 600 CCA	None	None		
<b>7. Alternator Min 125 Amp</b>	125	136	157		
<b>7a. Optional Alternator</b>	None	None	None		
<b>8. Power Steering</b>	Std	Std	Std		
<b>9. Mirrors Ext. Right/Left Side Swing Away, Power</b>	Opt	Opt	Std		
<b>10. Bumper, Rear Step Type Painted Mfg. Dealer Installed 400/4000 or Chrome</b>	Std	Std	Std		
<b>11. Radio AM/FM Factory Installed</b>	Std	AM/FM Stereo	AM/FM Stereo w/Digital Clock		

**TRUCK, 2 WHEEL DRIVE, EIGHT (8) FOOT BED**  
**2010 SPECIFICATIONS**

<b>Previous Std. Specs.</b>	<b>CHEVROLET / GMC</b>	<b>DODGE</b>	<b>FORD</b>		
<b>12. Dome Light</b>	Std	Std	Std		
<b>13. Carrier, Spare Wheel Underframe</b>	Std	Std w/spare	Std.		
<b>14. Air Conditioner Factory Installed</b>	Std	Std	Std		
<b>15. Tinted Glass All Windows</b>	Std	Std	Std		
<b>16. Power Outlet, 12V</b>	2 Outlets	1 Outlet	1 Outlets		
<b>17 Air Bag, Driver &amp; Passenger Sides</b>	Dual – Std	Dual – Std	Dual – Std		
<b>18 Fuel Tank - Single/ Dual 34 Gallon Min.</b>	34	35 Gal Std	38		

**TRUCK, 2 WHEEL DRIVE, EIGHT (8) FOOT BED  
2010 SPECIFICATIONS**

<b>Previous Std. Specs.</b>	<b>CHEVROLET / GMC</b>	<b>DODGE</b>	<b>FORD</b>		
<b>19. Shocks, Heavy Duty Front &amp; Rear</b>	Std	Std	Std		
<b>20. Vehicle to be Comp Winterized</b>	Std	Std	Std		
<b>21. Fuel ¼ Tank Upon Delivery</b>	Dealer	Dealer	Dealer		
<b>22. Standard Warranty 36/36</b>	3 Yr. 36,000 Mi 5 Yr 100,000 Mi Powertrain	3 Yr. 36,000 Mi	3 Yr. 36,000 Mi 5 Yr. 60,000 Mi Powertrain		
<b>Optional Equipment</b>					
<b>A. Differential Limited Slip</b>	Opt	Opt	Opt		
<b>B. Factory Paint Dark Green</b>	Opt	50 or More	Yes		

**TRUCK, 2 WHEEL DRIVE, EIGHT (8) FOOT BED**  
**2010 SPECIFICATIONS**

<b>Previous Std. Specs.</b>	<b>CHEVROLET / GMC</b>	<b>DODGE</b>	<b>FORD</b>		
<b>C. Optional Engine Size</b>	6.6L Diesel 365 3200 660 1600  B20 Capable	6.7 V6 Inline 6 Cummins Diesel 350 3000 350 1500  B5	6.8L V10 362 4750 457 3250  Diesel 6.4L 350 3000 650 2000		
<b>D. Sliding Glass Rear Window</b>	Dealer Opt Only	Opt	Opt		
<b>E. Transmission 4 Spd Auto w/Ext. Aux Transm Oil Cooler in Addition to Std</b>	6 Spd Opt - Cooler	4 Spd Auto	4 Spd Auto Oil to Air Std		
<b>F. Rear Axle Ratio</b>	3.73 Std 4.10 Opt	3.73 Std 4.10 Opt	3.73 Opt 4.10 Std with 5.4L Engine		